

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXR232HB-HBB

| Item Image | Wiring | Dimensions |
|---|--|--|
| | Abernative 2 way swatnering | Hemilton LINEA RONDO CFX R232 2 Way Rocker |
| | | |
| nsert Type | 3 gang 20AX 2 Way Rocker | |
| late Finish | Linea-Rondo CFX Connaught Bronze Frame/Connaught Bronze | |
| nsert Colour | Connaught Bronze/Black | |
| AN13 Barcode | 5017504058418 | |
| Dimensions (Nominal) | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm | |
| ixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| finimum Wall Box Depth | 35mm | |
| witched Poles | Single | |
| Current Rating | 20AX | |
| /oltage | 220/250V AC | |
| Maximum Load | 20 Amp inductive | |
| flains Frequency | 50Hz | |
| P Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Ferminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Ferminal Capacity 3 | 2 x 2.5mm2 | |
| Ferminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| erminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2 Linea-Rondo CFX is a UK Registered Design Certificate No: R: | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 04: |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio