

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXR23AB-ABB

Item Image Wiring Dimensions Hearnitton Javanese CRX	Linea-Rondo CFX Antique Brass Frame/Antique Brass Front 3 gang 10AX 2 Way Rocker Antique Brass/Black			
Primary Range Linea-Rondo CFX Insert Type 3 gang to AX 2 Way Rocker Peter Finish Linear Rondo CFX Insert Type 3 gang to AX 2 Way Rocker Peter Finish Linear Rondo CFX Antique Brass Frame/Antique Brass Insert Colour Antique Brass Black EANT 3 Barcode 5177404482237 Finish Bold Centres Barcode 5177404482237 Suitched Poles Contres Barcode 10AX Voltage 10AX			Dimensions	
Insert Type 3 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Antique Brass FramelAntique Brass Insert Colour Antique Frass/Black EAN13 Barcode 5017504482237 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Finish Hole Centres Box Fixing + 606.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp industive Mains Frequency 50Hz IP Rating IP ZXD Contact Gap Minimum 3mm Torminal Capacity 1 5 x 1mm2 Torminal Capacity 1 5 x 1mm2 Torminal Capacity 3 1 x 2.5mm2 Torminal Capacity 4 1 x 4mm2 Multi-strand Torminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 4.1.5mm2 Earth Terminal Capacity 3 1 x 4.1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 1.5mm2 Earth Terminal Capacity 9 1 x 1.5mm2 Earth Terminal Capacity 1 2 x 1.5mm2 Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x		Abernative 2 vary eventings	P23 2 Way Rocker	
Pate Finish				
Insert Colour		3 gang 10AX 2 Way Rocker		
EAN13 Barcode S017504482237	Plate Finish	Linea-Rondo CFX Antique Brass Frame/Antique Brass		
Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	Insert Colour	'		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips	EAN13 Barcode			
Minimum Wall Box Depth Single Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz PRating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5.x fmm2 Terminal Capacity 1 5.x fmm2 Terminal Capacity 1 1 x 2.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 5 x fmm2 Terminal Capacity 5 5 x fmm2 Terminal Capacity 5 5 x fmm2 Terminal Capacity 6 5 x fmm2 Earth Terminal Capacity 1 5 x fmm2 Earth Terminal Capacity 1 5 x fmm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x fmm2 Earth Terminal Capacity 6 1 x fmm2 Earth Terminal Capacity 8 1 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x fmm2 Earth Terminal Capacity	Dimensions (Nominal)			
Switched Poles Current Rating 10AX Voltage 120/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 1 x 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth T	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating Voltage 220/250V AC Maximum Load Maximum Load 10 Amp inductive 50Hz IP Rating IP2XD Contact Gap Minimum 3mm 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 In x 6mm2 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Cap	Minimum Wall Box Depth			
Voltage 220/250V AC Maximum Load 10 Amp Inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 4mm2 Multi-strand Earth Terminal Capacity 7 1x 4mm2 Multi-strand Earth Terminal Capacity 8 1x 4mm2 Multi-strand Earth Terminal Capacity 9 1x 6mm2 Froduct Class 1 5x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5x 0x40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Megistered Trade Mark No 2398667 Patents and Trademarks Linea is a Registered Trade Mark No 2398667 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All corrects are the time of going to press. BS EN ISO 901: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notics. Therefore, we reserve the right to alter designs and dimensions without prior notics. EXCE	Switched Poles	Single		
Maximum Load Mains Frequency 50Hz IP Rating IP Rati	Current Rating	10AX		
Mains Frequency Frequency Frating Frating Frequency Frequency Fresting Fresting Freminal Capacity 1 Freminal Capacity 2 Freminal Capacity 3 Freminal Capacity 3 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 5 Freminal Capacity 5 Freminal Capacity 1 Freminal Capacity 1 Freminal Capacity 1 Freminal Capacity 2 Freminal Capacity 2 Freminal Capacity 3 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 5 Freminal Capacity 4 Freminal Capacity 5 Freminal Capacity 5 Freminal Capacity 6 Freminal Capacity 6 Freminal Capacity 6 Freminal Capacity 7 Freminal Capacity 8 Freminal Capacity 8 Freminal Capacity 9 Fremi	Voltage	220/250V AC		
PRating	Maximum Load	10 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 4mm2 Multi-strand Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 I x 6mm2 Earth Terminal Capacity 7 Earth Terminal Capacity	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BESEN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM EXCOR	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BESIN SO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without pror notice. EBCE Due to manufacturing processes we cannot the BCE EBCE EBCE	Contact Gap Minimum	3mm		
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Todacity 4 Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dinensions without prior notice. BEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dinensions without prior notice. EXOC	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 6 Tx 4mm2 Multi-strand Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Tx 4mm2 Multi-strand Earth Terminal Capacity 8 Tx 4mm2 Multi-strand Earth Terminal Capacity 8 Tx 4mm2 Multi-strand Earth Terminal Capacity 9 Tx 4mm2 Multi-strand E	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All approducts listed conform to current British or European standard and the product information is correct at the time of going to press. BEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM E&CE	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot guarantee an exact colour match and shadings of EXCEPTION TO THE PROCESSOR OF THE PROCES	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04-07 PM EACH	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Ambient Operating Temperature Fecommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All stratement of going to press. BLIDEATE OF THE OFFICE OF THE OFFICE OF THE OFFICE OF THE OFFICE	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of EXCENTIAN Ammunity Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 2000m BS EN 6069-1 Linea is a Registered Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No: R21=2106349 SS2=2106350 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM EXCENTIAN EXAMPLE AND AMMUNITY Address and displayed and printing guarantee an exact colour match and shadings of	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM EACE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Product Class 1	Must be earthed		
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of CFX is a Registered Trade Mark No. 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 04:07 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio