## Hamilton

## making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio   |   |  |
|---|---|--|
| LRXR24PB-SSB<br>Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 4 gang 10AX 2 Way Rocker Polished Brass/Black  |   |  |
|   |   |  |
| li and the second s  |   | Hemilton<br>Linea Rondo CFX<br>R24<br>2 Way Rocker   |
|   | Image: specific specif |  |
| Primary Range   | Linea-Rondo CFX   |  |
| Insert Type   | 4 gang 10AX 2 Way Rocker  |  |
| Plate Finish  | Linea-Rondo CFX Polished Brass Frame/Satin Steel  |  |
| Insert Colour   | Polished Brass/Black  |  |
| EAN13 Barcode   | 5017504442248   |  |
| Dimensions (Nominal)  | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 25mm  |  |
| Switched Poles  | Single  |  |
| Current Rating  | 10AX  |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | 10 Amp inductive  |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 5 x 1mm2  |  |
| Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Terminal Capacity 3   | 1 x 2.5mm2  |  |
| Terminal Capacity 4   | 1 x 4mm2 Multi-strand   |  |
| Terminal Capacity 5   | 1 x 6mm2  |  |
| Earth Terminal Capacity 1   | 5 x 1mm2  |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Earth Terminal Capacity 2<br>Earth Terminal Capacity 3  | 4 x 1.5mm2<br>3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 3 x 2.5mm2<br>1 x 4mm2 Multi-strand   |  |
|   | 1 x 4mm2 // www.strand  |  |
| Earth Terminal Capacity 5   | Must be earthed   |  |
| Product Class 1   |   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS EN 60669-1   |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428<br>Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.   | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.   | Correct as at 16 October 2018 04:08 PM<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro:<br>T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off<br>E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in I | ad, Brislington, Bristol, BS4 5NZ<br>ice 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>ondon No. 941624 VAT Registration No. 222 6607 84  | Listed in STrimble DUCKINS Product Selector  |

SL

LRXR24PB-SSB - Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 4 gang 10AX 2 Way Rocker Polished Brass/Black

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio