

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

Linea-Rondo CFX Satin Nickel Frame/Bright Steel Front 4 gang 10AX 2 Way Rocker Satin Steel/Black Item Image	<u>LRXR24SN-BSB</u>			
Primary Range ILinea-Rondo CFX Insert Type ILinea-Rondo CFX Insert Type ILinea-Rondo CFX Insert Type ILinea-Rondo CFX Insert Colour Satin Steel/Black Insert Colour Satin Steel/Black EAN13 Barcode 5017504546243 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 10PX Minimum 10PX	Linea-Rondo CFX Satin Nickel	rame/Bright Steel Front 4 gang 10AX 2	Way Rocker Satin Steel/Black	
Primary Range Linea-Rondo CFX Insert Type Insert Type Insert Type Insert Colour EAN13 Barcode Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Winched Poles Single Current Rating 10AX Voltage 220/2560V AC Maximum Load Mains Frequency IP Rating IP2XD Contact Gap Minimum Image Linea-Rondo CFX Linea-Rondo Lin	Item Image	Wiring	Dimensions	
Insert Type 4 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Satin Nickel Frame/Bright Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504546243 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm			R24	
Insert Type 4 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Satin Nickel Frame/Bright Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504546243 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm		Afternative 2 vary swetching Use in Lose Out	91.5	
Plate Finish Linea-Rondo CFX Satin Nickel Frame/Bright Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504546243 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	ange Li	ea-Rondo CFX		
Insert Colour Satin Steel/Black EAN13 Barcode 5017504546243 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm	e 4	4 gang 10AX 2 Way Rocker		
EAN13 Barcode 5017504546243 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	sh Li	Linea-Rondo CFX Satin Nickel Frame/Bright Steel		
Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm	our S	Satin Steel/Black		
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	arcode 50	5017504546243		
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	ns (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm		
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	le Centres B			
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	Wall Box Depth 2 ^t			
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	Poles S			
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm				
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm	0			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm				
IP Rating IP2XD Contact Gap Minimum 3mm		· ·		
Contact Gap Minimum 3mm				
Terminal Capacity 2 4 x 1.5mm2				
		1 x 2.5mm2		
		1 x 4mm2 Multi-strand		
Terminal Capacity 5 1 x 6mm2				
Earth Terminal Capacity 1 5 x 1mm2	· · ·			
Earth Terminal Capacity 2 4 x 1.5mm2				
Earth Terminal Capacity 3 3 x 2.5mm2				
Earth Terminal Capacity 4	' '			
Earth Terminal Capacity 5 1 x 6mm2				
		Must be earthed		
		-5° to +40°C		
		Internal Use Only		
		2000m		
		BS EN 60669-1		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350	Li nd Trademarks C	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428		
All products listed conform to current British or European standard and the product information is All accessories are manufactured under an accredited European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme.	All products listed conform to current British or European standard and the product information is	All accessories are manufactured under an accredited	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 04:08 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio