

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LRXR26BC-BSW

Primary Range Linea-Rondo CFX Insert Type 6 gang 10AX 2 Way Rocker Insert Type 9 6 gang 10AX 2 Way Rocker Insert Clour Bright Chrome-White EAN13 Barcode 5017504507206 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand	Dimensions  Hemilton LINEA RONDO CFX R26 2 Way Rocker
Primary Range Linea-Rondo CFX Insert Type 6 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Bright Chrome Frame/Bright Steel Insert Colour EAN13 Barcode Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load Maximum Load Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 1 x 4.5mm2 Terminal Capacity 4 Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	R26
Insert Type	
Plate Finish  Linea-Rondo CFX Bright Chrome Frame/Bright Steel  Insert Colour  Bright Chrome/White  EAN13 Barcode  5017504507206  Dimensions (Nominal)  Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 120.6mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  25mm  Switched Poles  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2	
Insert Colour  EAN13 Barcode  Dimensions (Nominal)  Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 120.6mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Switched Poles  Current Rating  Voltage  Voltage  Maximum Load  Mains Frequency  IP Rating  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Eart	
EAN13 Barcode         5017504507206           Dimensions (Nominal)         Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm           Fixing Hole Centres         Box Fixing = 120.6mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Dimensions (Nominal)  Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 120.6mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  IP Rating  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3	
Fixing Hole Centres  Minimum Wall Box Depth  25mm  Switched Poles  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  Mains Frequency  IP Rating  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 2  Earth Terminal Capacity 3	
Minimum Wall Box Depth  Switched Poles  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 2  4 x 1.5mm2  5 x 1mm2  5 x 1mm2  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 2  4 x 1.5mm2  5 x 1mm2	
Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2	
Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Maximum Load       10 Amp inductive         Mains Frequency       50Hz         IP Rating       IP2XD         Contact Gap Minimum       3mm         Terminal Capacity 1       5 x 1mm2         Terminal Capacity 2       4 x 1.5mm2         Terminal Capacity 3       1 x 2.5mm2         Terminal Capacity 4       1 x 4mm2 Multi-strand         Terminal Capacity 5       1 x 6mm2         Earth Terminal Capacity 1       5 x 1mm2         Earth Terminal Capacity 2       4 x 1.5mm2         Earth Terminal Capacity 3       3 x 2.5mm2	
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
IP Rating	
Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Terminal Capacity 2       4 x 1.5mm2         Terminal Capacity 3       1 x 2.5mm2         Terminal Capacity 4       1 x 4mm2 Multi-strand         Terminal Capacity 5       1 x 6mm2         Earth Terminal Capacity 1       5 x 1mm2         Earth Terminal Capacity 2       4 x 1.5mm2         Earth Terminal Capacity 3       3 x 2.5mm2	
Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2	
Earth Terminal Capacity 3 3 x 2.5mm2	
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5 1 x 6mm2	
Product Class 1 Must be earthed	
Ambient Operating Temperature -5° to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 238337  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=21	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products
Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding.  R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio