

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXR26SB-SSW

Item Image Wiring Dimensions Hamilton Live Rocko OX Taysu	Linea-Rondo CFX Satin Brass Frame/Satin Steel Front 6 gang 10AX 2 Way Rocker Satin Brass/White			
Primary Range Linea-Rendo CFX Insert Type Spane (Linea-Rendo CFX) Insert Type (Linea				
Insert Type		Alternative 2 very switching	R26	
Plate Finish Linear Colour Satin Brass/White EAN13 Barcode Soft Syd-463206 Dimensions (Nominal) Double: Height = 91.5mm Width = 190.5mm Depth = 4.0mm Fixing Hole Centres Bay Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Zomm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp Inductive Mains Frequency 19 Rating 192XD Contact Gap Minimum Samm Terminal Capacity 1 5.1mm2 Terminal Capacity 2 1x.5mm2 Terminal Capacity 3 1x.25mm2 Terminal Capacity 4 1x.4mm2 Multi-strand Terminal Capacity 1 5x.1mm2 Earth Terminal Capacity 1 5x.1mm2 Earth Terminal Capacity 3 3x.2.5mm2 Earth Terminal Capacity 3 1x.6mm2 Earth Terminal Capacity 5 1x.6mm2 Earth Terminal Capacity 5 1x.6mm2 Earth Terminal Capacity 6 1x.6mm2 Earth Terminal Capacity 7 1x.6mm2 Earth Terminal Capacity 8 1x.6mm2 Earth Terminal Capacity 9 1x.6mm2 Ear				
Satin BrassWhite		<u> </u>		
EAN13 Barcode S017504463205 Dunesions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm	Plate Finish			
Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Holo Centres Box Fixing = 120.6mm Grid Fixing = CPX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 110 Amp Inductive Mains Frequency 15P Rating 15	Insert Colour			
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips	EAN13 Barcode			
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency Fe Rating IPEXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Termin	Dimensions (Nominal)			
Switched Poles Current Rating 10AX Voltage 10AC Voltage 10 Amp inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 1x 4mm2 Multi-strand Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacit	Fixing Hole Centres			
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm IP2XD Contact Gap Minimum 5 x 1 mm2 Terminal Capacity 1 5 x 1 mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 8 1 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x 6mm2 Earth Te	Minimum Wall Box Depth			
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4.5mm2 Earth Terminal Capacity 6 1x 6mm2 Earth Terminal Capacity 7 1x 4mm2 Multi-strand Earth Terminal Capacity 8 1x 4.5mm2 Earth Terminal Capacity 9 1x 4 1x 4.5mm2 Earth Terminal Capacity 9 1x 6mm2 Froduct Class 1 1 5** 0 1x 6mm2 Froduct Class 1 Must be earthed 5** 0 1x 6mm2 Froduct Class 1 1 Must be earthed 5** 0 1x 6mm2 Froduct Class 1 1 1x 6mm2 Froduct Class 1 1x 6m	Switched Poles	Single		
Maximum Load Mains Frequency 50Hz IP Rating IP Rati	Current Rating			
Mains Frequency Frequency Fresting Fresting	Voltage			
PRating IP2XD	Maximum Load	10 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity	Mains Frequency			
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5° to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 S82=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BY EN IND 9001: 2015 Quality Management System. BY EN Ind Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 S82=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BY EN IND 9001: 2015 Quality Management System. BY EN IND 9001: 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of EXOE	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Abbient Operating Temperature 5-5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BAIL products listed conform to current British or European standard and the product information is correct at the time of going to press. BAIL products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot the feedings and dimensions without prior notice. EXOME EXOME Correct as at 16 October 2018 04-08 PM: EXOME EXOME EXOME EXOME Correct as at 16 October 2018 04-08 PM: EXOME EXOME EXOME EXOME EXOME Correct as at 16 October 2018 04-08 PM: EXOME EXO	Contact Gap Minimum	3mm		
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 To femm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Z000m Standard/Approval Est N 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No. R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BSEN ISO 9001 : 2015 Quality Management System. BSEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BSEN ISO 9001 : 2015 Quality Management System. Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:08 PM Exote Correct as at 16 October 2018 04:0	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as spart of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Correct as at 16 October 2018 04:08 PM E&O	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E806	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 In x 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM: E&CD	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Excellence.	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 6069-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products and diagrams are reproduced within the limitations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Exception All x 4mm2 Multi-strand 1 x 4mm2 1 x 6mm2 2000m ESCEN EVALUATE: All Accessories are manufactured under an accredited as part of our devlopment programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCEN ESCEN Correct as at 16 October 2018 04:08 PM. ESCEN ESCE	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&CE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&OE	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Upuarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&OE	Product Class 1	Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&OE	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&OE	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PM E&OE	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:08 PN E&OE	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 04:08 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio