# Hamilton

### making connections beautifully

SL

Insert Type1 gang 10AX Push To Make/Push to Break Retractive RockerPlate FinishLinea-Rondo CFX Polished Brass Frame/Satin BrassInsert ColourPolished Brass/WhiteEAN13 Barcode5017504413194Dimensions (Nominal)Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimum Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 31 x 4mm2 Multi-strandTerminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth T	Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio					
Linea-Rondo CFX Polished Brass Frame/Satin Brass Front 1 gang 10AX Push To Make/Push to Break Retractive Rocker Polished Brass/White Uring Uring Urin	LRXRRTPB-SBW					
Image in the im	Linea-Rondo CFX Polished Brass Frame/Satin Brass Front 1 gang 10AX Push To Make/Push to Break Retractive Rocker					
Image SeriesImage Series </td <td>Item Image</td> <td>Wiring</td> <td>Dimensions</td>	Item Image	Wiring	Dimensions			
Insert Type1 gang 10AX Push To Make/Push to Break Retractive RockerPiate FinishLinea-Rondo CFX Polished Brass Frame/Satin BrassInsert ColourPolished Brass/WhiteEAN13 Barcode5017504113194Dimensions (Nominal)Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimum Wall Bix Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage202050V ACMaximum Load10 Amp inductiveMain Marking50HzIP Rating192XDConted Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 31 x 4mm2 Multi-strandTerminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 43 x 2.5mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Freedom Componention1 kernel Use OnlyMaximun Insta			LINEA RONDO CFX CCRRT Push to Make/Push to Break Retractive Rocker			
Plate FinishLinea-Rondo CFX Polished Brass Frame/Satin BrassInsert ColourPolished Brass/WhiteEAN13 Barcode5017504413194Dimensions (Nominal)Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimur Wall Box DepthZimmSwitched PolesSingleCurrent Rating10AXVoltage220250V ACMaximur Load10 Amp inductiveMains Frequency50HzIP RatingIP 2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity	Primary Range	Linea-Rondo CFX				
Insert ColourPolished Brass/WhiteEAN13 Barcode5017504413194Dimensions (Nominal)Single: Height = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimur Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage202050V ACMaximur Load10 Amp inductiveMainur Srequency50HzP RatingIP2XDCortact Gap Minimur3mmTerminal Capacity 15 x Imm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Earth Terminal Capacity 15 x Imm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 61 x 6mm2	Insert Type	1 gang 10AX Push To Make/Push to Break Retractive Rocker				
EAN13 Barcode5017504413194Dimensions (Nominal)Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Exing = 60.3mm Grid Fixing = CFX ClipsMinimur Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximur Load10 Amp inductiveMains Frequency50HzP RatingIP2XDContage Lapacity 15x 1mm2Terminal Capacity 15x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 5mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 31 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2Earth Terminal Capacity 51 x 4mm2Earth Terminal Capacity 41 x 4mm2Earth Terminal Capacity 51 x 4mm2Earth Terminal Capacity 61 x 4mm2Earth Terminal Capacity 71 x 4mm2Earth Terminal Capacity 6 <t< td=""><td>Plate Finish</td><td colspan="3">Linea-Rondo CFX Polished Brass Frame/Satin Brass</td></t<>	Plate Finish	Linea-Rondo CFX Polished Brass Frame/Satin Brass				
Dimensions (Nominal)Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimu Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzP RatingIPZXDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 4mm2 Multi-strandTerminal Capacity 15 x 1mm2Terminal Capacity 15 x 1mm2Terminal Capacity 31 x 4mm2 Multi-strandTerminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Terminal Capacity 41 x 6mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 74 x 1.5mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 81 x 6mm2Earth Terminal Capacity 9 <t< td=""><td>Insert Colour</td><td colspan="3">Polished Brass/White</td></t<>	Insert Colour	Polished Brass/White				
Fixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimum Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 4mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capac	EAN13 Barcode	5017504413194				
Minimum Wall Box Depth   25mm     Switched Poles   Single     Current Rating   10Ax     Voltage   20250V AC     Maximum Load   10 Amp inductive     Mains Frequency   50Hz     IP Rating   IP2XD     Contact Gap Minimum   3mm     Terminal Capacity 1   5 x 1mm2     Terminal Capacity 2   4 x 1.5mm2     Terminal Capacity 3   1 x 2.5mm2     Terminal Capacity 4   1 x 4mm2 Multi-strand     Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 1   5 x 1mm2     Terminal Capacity 4   1 x 4mm2 Multi-strand     Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 4   1 x 4mm2 Multi-strand     Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 4   1 x 4mm2 Multi-strand     Earth Terminal Capacity 4   1 x 4mm2 Multi-strand     Earth Terminal Capacity 5   1 x 6mm2     Forduct Class 1   Mustbe earthed <td< td=""><td>Dimensions (Nominal)</td><td colspan="3">Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm</td></td<>	Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm				
Switched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximun Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmContact Gap Minimum5x 1mm2Terminal Capacity 15 x 1mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Terminal Capacity 31 x 6mm2Earth Terminal Capacity 15 x 1mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips				
Current Rating10AXVoltage220/250V ACMaximur Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Terminal Capacity 15 x 1mm2Terminal Capacity 31 x 4.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 53 x 2.5mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 54 x 1.5mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 74 x 1.5mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 61 x 6mm2Product Class 1Must be earthedAmbint Operating Temperature-5' to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Minimum Wall Box Depth					
Voltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 75 x 1mm2Earth Terminal Capacity 81 x 4mm2 Multi-strandEarth Terminal Capacity 91 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 75 x 1mm2Earth Terminal Capacity 81 x 6mm2Earth Terminal Capacity 95 x 1 x 6mm2Earth Terminal Capacity 91 x 4mm2 Multi-strandEarth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 81 x 6mm2Earth Terminal Capacity 92 x 0.5mm2Earth Terminal Capacity 92 x 0.5mm2Earth Terminal Capacity 9	Switched Poles	Single				
Name10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 1.5mm2Earth Terminal Capacity 51 x 6mm2Product Class 11 x 6mm2Multi-strand1 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 55 x 1mm2Earth Terminal Capacity 65 x 1mm2Earth Terminal Capacity 75 x 10mm2Earth Terminal Capacity 61 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Current Rating					
Mains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 31 x 6mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Forduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Voltage					
IP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Maximum Load	10 Amp inductive				
O Contact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Mains Frequency					
Terminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 53 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	IP Rating	IP2XD				
Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Contact Gap Minimum					
Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Terminal Capacity 1					
Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Terminal Capacity 2	4 x 1.5mm2				
Terminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Terminal Capacity 3	1 x 2.5mm2				
Terminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Terminal Capacity 4	1 x 4mm2 Multi-strand				
Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Terminal Capacity 5					
Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Earth Terminal Capacity 1					
Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Earth Terminal Capacity 2					
Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Earth Terminal Capacity 3					
Product Class 1 Must be earthed   Ambient Operating Temperature -5° to +40°C   Recommended Location Internal Use Only   Maximum Installation Altitude 2000m	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand				
Product Class 1 Must be earthed   Ambient Operating Temperature -5° to +40°C   Recommended Location Internal Use Only   Maximum Installation Altitude 2000m	Earth Terminal Capacity 5					
Ambient Operating Temperature -5° to +40°C   Recommended Location Internal Use Only   Maximum Installation Altitude 2000m	Product Class 1	Must be earthed				
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m	Ambient Operating Temperature					
Maximum Installation Altitude 2000m		Internal Use Only				
Standard/Approval BS EN 60669-1	Maximum Installation Altitude					

# Hamilton

### making connections beautifully

Wining Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

#### LRXRRTPB-SBW

#### Linea-Rondo CFX Polished Brass Frame/Satin Brass Front 1 gang 10AX Push To Make/Push to Break Retractive Rocker Polished Brass/White

Linea is a Registered Trade Mark No 2309665

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. ( Linea-Rondo CFX is a UK Registered Design Certificate N	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 04:09 PM E&OE
	d, Brislington, Bristol, BS4 5NZ ce 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	A Listed in Trimble Contraction of the product selector

SL