Hamilton

making connections beautifully

SL

Wring Accessories - Circuit Protection - Smart Lighting Control & Multi-room Audio Linea-Rondo CFX Satin Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black ltem Image Wiring Dimensions If the Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image			and the local and the second sec							
Linea-Rondo CFX Satin Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black Item Image Dimensions If the Image Image Image	성기의 동안에 가 못 먹었는 것 같아. 것이라고 있는 것 같아?	Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio								
Item Image Wiring Image Image		LRXSHSSB-SBB								
Primary Range Linea-Rondo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Pate Finish Linea-Rondo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Pate Finish Linea-Rondo CFX Vertical Satin Brass Insert Colour Black EAN13 Barcode 501750/451035 Dimensions (Nominal) Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm Fixing 140e Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Armm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 00/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 5 x tmm2	Linea-Rondo CFX Satin Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black									
Primary Range Linea-Rondo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Linea-Rondo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Linea-Rondo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Linea-Rondo CFX Vertical Satin Brass Insert Topic Black EAN13 Barcode S017504451035 Dimensionel (Nominal) Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm Fixing Helo Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 200/250V input; 115/230V 20VA output Masimum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IPXD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2	Item Image	Wiring	Dimensions							
Insert TypeShaver Dual Voltage Unswitched Socket (Vertically Mounted)Plate FinishLinea-Rondo CFX Vertical Satin Brass Frame/Satin BrassInsert ColourBlackEAN13 Barcode5017504451035Dimensions (Nominal)Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2			SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted)							
Plate FinishLinea-Rondo CFX Vertical Satin Brass Frame/Satin BrassInsert ColourBlackEAN13 Barcode5017504451035Dimensions (Nominal)Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	Primary Range	Linea-Rondo CFX								
Insert ColourBlackEAN13 Barcode5017504451035Dimensions (Nominal)Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)								
EAN13 Barcode5017504451035Dimensions (Nominal)Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	Plate Finish	Linea-Rondo CFX Vertical Satin Brass Frame/Satin Brass								
Dimensions (Nominal)Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mmFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	Insert Colour	Black								
Fixing Hole CentresBox Fixing = 120.6mmGrid Fixing = CFX ClipsMinimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	EAN13 Barcode	5017504451035								
Minimum Wall Box Depth47mmSwitched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	Dimensions (Nominal)	Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mr	n							
Switched PolesNoneCurrent Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2										
Current Rating20VAVoltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2										
Voltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2										
Voltage220/250V ACMaximum Load200/250V input; 115/230V 20VA outputMains Frequency50HzIP RatingIP2XDContact Gap MinimumNoneTerminal Capacity 15 x 1mm2	Current Rating									
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2		/250V AC								
IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2	Maximum Load	200/250V input; 115/230V 20VA output								
Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2	Mains Frequency	50Hz								
Terminal Capacity 1 5 x 1mm2	IP Rating	IP2XD								
	Contact Gap Minimum	None								
Terminal Capacity 2 4 x 1.5mm2	Terminal Capacity 1	5 x 1mm2								
	Terminal Capacity 2	4 x 1.5mm2								
Terminal Capacity 3 3 x 2.5mm2	Terminal Capacity 3	3 x 2.5mm2								
Terminal Capacity 4 2 x 4mm2 Multi-strand	Terminal Capacity 4	2 x 4mm2 Multi-strand								
Terminal Capacity 5 1 x 6mm2	Terminal Capacity 5	1 x 6mm2								
Earth Terminal Capacity 1 9 x 1mm2	Earth Terminal Capacity 1	9 x 1mm2								
Earth Terminal Capacity 2 6 x 1.5mm2	Earth Terminal Capacity 2	6 x 1.5mm2								
Earth Terminal Capacity 3 4 x 2.5mm2	Earth Terminal Capacity 3	4 x 2.5mm2								
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand								
Earth Terminal Capacity 5 1 x 6mm2	Earth Terminal Capacity 5	1 x 6mm2								
Product Class 1 Must be earthed	Product Class 1 Must be earthed									
Ambient Operating Temperature -5° to +40°C	Ambient Operating Temperature	-5° to +40°C								
Recommended Location Internal Use Only	Recommended Location	Internal Use Only								
Maximum Installation Altitude 2000m	Maximum Installation Altitude	2000m								
Standard/Approval BS EN 61558-2-5 - BS 4573										
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm										

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXSHSSB-SBB

Linea-Rondo CFX Satin Brass Frame/Sa	atin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black
	Linea is a Registered Trade Mark No 2398665

	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350			
	All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
	Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.			Correct as at 16 October 2018 04:09 PM E&OE
		ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB .ondon No. 941624 VAT Registration No. 222 6607 84		Listed in Trimble	riba product selector

SL