

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXSS2AB-ABB

Linea-Rondo CFX Antique Brass Frame/Antique Brass Front 2 gang 13A Double Pole Switched Socket Antique Brass/Black

Item Image Wiring **Dimensions** Hamilton SS2 Switched Socket Primary Range Linea-Rondo CFX Insert Type 2 gang 13A Double Pole Switched Socket Plate Finish Linea-Rondo CFX Antique Brass Frame/Antique Brass Insert Colour Antique Brass/Black EAN13 Barcode 5017504482022 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double **Current Rating** 13 Amp 220/250V AC Voltage Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2 5mm2 Terminal Capacity 2 3 x 4mm2 2 x 6mm2 Multi-Strand **Terminal Capacity 3** Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2 Additional Notes Dual Earth: Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Patents and Trademarks Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice. correct at the time of going to press. Correct as at 16 October 2018 04:10 PM Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot guarantee an exact colour match and shadings of the limitations of reproduction and printing process and are not binding. of certain finishes

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com_www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio