Hamilton

making connections beautifully

Insert Type 1 gang	Wiring Image: Control of the second	A Triple Pole Rocker White/White Dimensions HEINEA RONDO CFX TP Triple Pole Rocker
Item Image Image Primary Range Insert Type 1 gang	Rondo CFX Rondo CFX Rondo CFX Satin Nickel Frame/Satin Steel White	Dimensions Hemilton LINEA RONDO CFX TP Triple Pole Rocker
Item Image Image Primary Range Linea-F Insert Type 1 gang	Wiring Image: Control of the second	Dimensions Hemilton LINEA RONDO CFX TP Triple Pole Rocker
Primary Range Linea-F Insert Type 1 gang	Rondo CFX Rondo CFX Satin Nickel Frame/Satin Steel White	HEINILON LINEA RONDO CFX TP Triple Pole Rocker
Insert Type 1 gang	10A Triple Pole Rocker Rondo CFX Satin Nickel Frame/Satin Steel White	Triple Pole Rocker
Insert Type 1 gang	10A Triple Pole Rocker Rondo CFX Satin Nickel Frame/Satin Steel White	Triple Pole Rocker
Insert Type 1 gang	10A Triple Pole Rocker Rondo CFX Satin Nickel Frame/Satin Steel White	
Insert Type 1 gang	10A Triple Pole Rocker Rondo CFX Satin Nickel Frame/Satin Steel White	
	Rondo CFX Satin Nickel Frame/Satin Steel White	
Plate Finish Linea-F	White	
Insert Colour White/W	04520502	
EAN13 Barcode 501750		
Dimensions (Nominal) Single:	Height = 91.5mm Width = 91.5mm Depth =	= 4.0mm
Fixing Hole Centres Box Fix	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth 25mm		
Switched Poles Triple		
Current Rating 10A		
Voltage 220/250	OV AC	
Maximum Load 10 Amp	p resistive	
Mains Frequency 50Hz		
IP Rating IP2XD		
Contact Gap Minimum 3mm		
Terminal Capacity 1 5 x 1mr	m2	
Terminal Capacity 2 4 x 1.5r	mm2	
Terminal Capacity 3 1 x 2.5r	mm2	
Terminal Capacity 4 1 x 4mr	m2 Multi-strand	
Terminal Capacity 5 1 x 6mr	m2	
Earth Terminal Capacity 1 5 x 1mr	m2	
Earth Terminal Capacity 2 4 x 1.5r	mm2	
Earth Terminal Capacity 3 3 x 2.5r	mm2	
Earth Terminal Capacity 4 1 x 4mr	m2 Multi-strand	
Earth Terminal Capacity 5 1 x 6mr	m2	
Product Class 1 Must be	e earthed	
Ambient Operating Temperature -5° to +	+40°C	
Recommended Location Internal	I Use Only	
Maximum Installation Altitude 2000m	I	
Standard/Approval BS EN	60669-1	
Patents and Trademarks CFX is	s a Registered Trade Mark No 2398665 a Registered Trade Mark No 2398667 Patent I Rondo CFX is a UK Registered Design Certifica	No. GB 2383375B Community Trd Mark No. 002906428 ate No: R21=2106349 SS2=2106350
	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 04:11 P E&O

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio