SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


LRXTVSATBC-BSW

Linea-Rondo CFX Bright Chrome Frame/Bright Steel Front 2 gang Non-Isolated TV+Satellite 2in/2out White


Item Image







Dimensions



the limitations of reproduction and printing guarantee an exact colour match and shadings of			
Plate Finish Linea-Rondo CFX Bright Chrome Frame/Bright Steel Insert Colour White EAN13 Barcode 5017504500689 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Minimum Wall Box Depth 35mm Minimum Wall Box Depth N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 Dimension of the product information is a part of under an accredited and the product of the company to improve products and dimensions without prior notice. BESEN ISO 9001: 2015 Quality Management System Therefore, we reserve the right to alter d	Primary Range	Linea-Rondo CFX	
Insert Colour White EAN13 Barcode 5017504500689 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a 18 Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business Registered Trade Mark No. 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exerce colour match a shading of	Insert Type	2 gang Non-Isolated TV+Satellite 2in/2out	
EAN13 Barcode 5017504500689 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Multi-strand Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea & Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bus NS 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Bus NS 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Plate Finish	Linea-Rondo CFX Bright Chrome Frame/Bright Steel	
Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks Linea-Rondo CFX is a UK Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a W Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All secsories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Therefore, we reserve the right to after designs and dimensions without prior notice. Therefore, we reserve the right to after designs and dimensions without prior notice. Therefore, we reserve the right to after designs and dimensions without prior notice. Therefore, we reserve the right to after designs and dimensions without prior notice. Therefore, we reserve the right to after designs and dimensions without prior notice.	Insert Colour	White	
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm N/A IP Rating IP Rating IP SXD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Ix 6mm2 Earth Terminal Capacity 5 Ix 6mm2 Earth Terminal Capacity 5 Ix 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Ix 6mm2 Earth Terminal Capacity 6 Ix 6mm2 Earth Terminal Capacity 6 Ix 6mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Ix 6mm2 Earth Terminal Capacity 8 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2 Ix 6mm2 Earth Terminal Capacity 9 Ix 6mm2	EAN13 Barcode	5017504500689	
Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks CPX is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No. R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 · 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 · 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot Correct as at 16 October 2018 04:	Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Switched Poles N/A IP Rating IP 2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m CFX is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited It is the policy of the company to improve products a spart of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BEN ISO 9001 : 2015 Quality Management System. Correct as at 16 October 2018 04: Union of the imitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04: Correct as at 16 October 2018 04:	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
IP Rating Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 In x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Be N ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot Correct as at 16 October 2018 04: guarantee an exact colour match and shadings of	Minimum Wall Box Depth	35mm	
Contact Gap Minimum Rarth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Bue to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04: 9urantee an exact colour match and shadings of	Switched Poles	N/A	
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	IP Rating	IP2XD	
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of	Contact Gap Minimum	N/A	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing Bark Amm2 Must be earthed (ref BS7671 415.2.1) Must be earthed (ref BS7671 415.2.1) All product Class 1 Must be earthed (ref BS7671 415.2.1) Internal Use Only 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:	Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:	Earth Terminal Capacity 3	3 x 2.5mm2	
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:	Earth Terminal Capacity 5	1 x 6mm2	
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of	Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:	Ambient Operating Temperature	-5° to +40°C	
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04: guarantee an exact colour match and shadings of	Recommended Location	Internal Use Only	
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. BS EN ISO 9001: 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of	Maximum Installation Altitude	2000m	
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428	
the limitations of reproduction and printing guarantee an exact colour match and shadings of	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs
process and an extension of the contract of th		Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 04:11 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1779 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered of London No. 941624 VAT Registration No. 222 6607 84









