Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
	LRXUS5SB-SSW	
Linea-Rondo CFX Satin Brass Frame/Satin Steel Front 1 gang 5A Unswitched Socket White		
Linea-Rondo Cr X Satin Blass Frame/Satin Steer From Figang SX Onswitched Socket White		
Item Image	Wiring	Dimensions
	Neutral. Earth Live	HEIDELINE AUS Unswitched Socket
Drimon (Bongo	Linea-Rondo CFX	
Primary Range		
Insert Type	1 gang 5A Unswitched Socket	
Plate Finish	Linea-Rondo CFX Satin Brass Frame/Satin Steel White	
Insert Colour	5017504460051	
EAN13 Barcode	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Dimensions (Nominal)	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Fixing Hole Centres	35mm	
Minimum Wall Box Depth Switched Poles	None	
	5 Amp	
Current Rating Voltage	220/250V AC	
Maximum Load	5 Amp	
Maximum Load Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	2 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 546	
Additional Notes	Shuttered: Yes	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 04:12 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered office 1 Rushmills, Bedford Road, Northampton NN2 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84		

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio