Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LSX1GPBC-PB Linea-Scala CFX Grid-IT Bright Chrome Frame/Polished Brass Front 1 Gang Grid Fix Aperture Plate with Grid Item Image Wiring Dimensions Hemilton 1GP Single plate with 1 x GRID-IT cutout 91.5 GRID-IT Primary Range Insert Type 1 Gang Grid Fix Aperture Plate with Grid Plate Finish Linea-Scala CFX GRID-IT Bright Chrome Frame/Polished Brass Insert Colour No Insert Colour EAN13 Barcode 5017504074364 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Box Fixing = 60.3mm Grid Fixing = CFX Clips **Fixing Hole Centres** Minimum Wall Box Depth As Per Insert Switched Poles N/A IP Rating N/A N/A Contact Gap Minimum Earth Terminal Capacity 1 11mm2 Product Class 1 Face plate must be earthed **Recommended Location** Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:56 AM E&OE process and are not binding of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in Trimble SECA T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

SL