Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LSX1XLEDITB100BK-BS Linea-Scala CFX Black Nickel Frame/Bright Steel 1g 100W LED 2 Way Push On/Off Rotary Dimmer Black Nickel Item Image Wiring Dimensions Hemilton 1XLEDITB LEDITB100 2 Way Dimme Linea-Scala CFX Primary Range Insert Type 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Scala CFX Black Nickel Frame/Bright Steel Insert Colour Black Nickel EAN13 Barcode 5017504085117 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) 50Hz Mains Frequency IP Rating IP2XD **Terminal Capacity 1** 2X1mm² **Terminal Capacity 2** 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed -5°C to +40°C Ambient Operating Temperature Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 17 October 2018 08:31 AM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding. of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in Trimble **SECA** T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 E: info@hamilton-litestat.com www.hamilton-litestat.com

SL