

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSX1XLEDITB100RB-RB

Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze 1g 100W LED 2 Way Push On/Off Rotary Dimmer Richmond Bronze

Bronze		
Item Image	Wiring	Dimensions
		Hamilton LINEA SCALA CFX 1XLEDITB LEDITB100 2 Way Dimmer
		91.5
Primary Range	Linea-Scala CFX	
Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer	
Plate Finish	Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze	
Insert Colour	Richmond Bronze	
EAN13 Barcode	5017504085216	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Wattage	5-100W (10 LED Lamps MAX)	
Switched Poles	Single	
Current Rating	0.4A	
Voltage	230V-240V	
Maximum Load	5-100W (10 LED Lamps MAX)	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Terminal Capacity 1	2X1mm²	
Terminal Capacity 2	2X1.5mm ²	
Earth Terminal Capacity 1	5X1mm²	
Earth Terminal Capacity 2	4X1.5mm²	
Earth Terminal Capacity 3	3X2.5mm²	
Earth Terminal Capacity 4	1X4mm² Multi-Strand	
Earth Terminal Capacity 5	1X6mm²	
Product Class 1	Face plate muct be earthed	
Ambient Operating Temperature	-5°C to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Trailing Edge & Leading Edge Dimmer	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:31 AN E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio