SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSX2J12BC-BSW

| Linea-Scala CFX Bright Chrome Frame/Bright Steel Front 2 gang RJ12 Outlet - Unshielded White  |   |  |
|---|---|--|
| Item Image  | Wiring  | Dimensions   |
|   | Detacom Module Rear View  RJ11/12 Socket Rear View  Cable tie  anchor  Sister Life Transparent Cover  1 2 3 4 5 0 0  Sister Life Transparent Cover  Sister | LINEA SCALA CFX 2.12 2 gang RJ12 Outlet Unshielded 6 wire  |
| Primary Range   | Linea-Scala CFX   |  |
| Insert Type   | 2 gang RJ12 Outlet - Unshielded   |  |
| Plate Finish  | Linea-Scala CFX Bright Chrome Frame/Bright Steel  |  |
| Insert Colour   | White   |  |
| EAN13 Barcode   | 5017504700560   |  |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth  | 35mm  |  |
| Switched Poles  | N/A   |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | N/A   |  |
| Earth Terminal Capacity 1   | 5 x 1mm2  |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)  |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| EuroFix Additional Notes  | Can be used as either RJ11 (4 wires) or RJ12 (6 wires)  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.  Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.   | Correct as at 17 October 2018 08:32 AM E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











