Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LSX2J12SB-SSB Linea-Scala CFX Satin Brass Frame/Satin Steel Front 2 gang RJ12 Outlet - Unshielded Black Item Image Wiring Dimensions Hemilton 2J12 2 gang RJ12 Outlet Unshielded 6 wire Datacom Module Rear View RJ11 / 12 Socket Rear View 91.5 Cable tie 25.0 - 25.0 Linea-Scala CFX Primary Range Insert Type 2 gang RJ12 Outlet - Unshielded Plate Finish Linea-Scala CFX Satin Brass Frame/Satin Steel Insert Colour Black EAN13 Barcode 5017504661564 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Box Fixing = 60.3mm Grid Fixing = CFX Clips Fixing Hole Centres Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 -5° to +40°C Ambient Operating Temperature Internal Use Only Recommended Location Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used as either RJ11 (4 wires) or RJ12 (6 wires) Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:32 AM E&OE process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ SECA Listed in Trimble T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 LUCKINS

SL