SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSX2J45SN-BSB

Linea-Scala CFX Satin Nickel Frame/Bright Steel Front 2 gang RJ45 CAT 5E Outlet - Unshielded Black

## Item Image Wiring **Dimensions** Hamilton 2J45 2 gang RJ45 - CAT 5E Outlet Unshielded 8 wire Linea-Scala CFX Primary Range Insert Type 2 gang RJ45 CAT 5E Outlet - Unshielded Plate Finish Linea-Scala CFX Satin Nickel Frame/Bright Steel Insert Colour Black EAN13 Barcode 5017504741587 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2

3 x 2.5mm2

1 x 6mm2

-5° to +40°C

2000m

Internal Use Only

1 x 4mm2 Multi-strand

Must be earthed (ref BS7671 415.2.1)

Linea is a Registered Trade Mark No 2398665

Can be used in both EIA 568A and EIA 568B wiriing schedules

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B

Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

It is the policy of the company to improve products as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 08:32 AM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.

Earth Terminal Capacity 3

Earth Terminal Capacity 4

Earth Terminal Capacity 5

Recommended Location Maximum Installation Altitude

EuroFix Additional Notes

Patents and Trademarks

**Ambient Operating Temperature** 

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









