Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio		
LSX2J45SN-BSW		
Linea-Scala CFX Satin Nickel Frame/Bright Steel Front 2 gang RJ45 CAT 5E Outlet - Unshielded White		
Linea-Scala Cr X Satin Nickel Hame/Bright Steer Hont 2 gang 1045 CAT 5L Outlet - Chisnieided White		
Item Image	Wiring	Dimensions
	RJ45 CAT5e Rear View	ELEA SCALA CFX 245 2 gang R145 - CAT SE Outlet Unshielded 8 wire
Primary Range	Linea-Scala CFX	
Insert Type	2 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Linea-Scala CFX Satin Nickel Frame/Bright Steel	
Insert Colour	White	
EAN13 Barcode	5017504740580	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
	4 x 1.5mm2	
Earth Terminal Capacity 2 Earth Terminal Capacity 3	3 x 2.5mm2	
	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5		
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:32 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in MTrimble product selector

SL