




LSX2XTSRB-RBB

Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze Front 2 gang Multi-Way Touch Slave Controller Black Nickel/Black

Item Image	Wiring	Dimensions			
					
			Primary Range	Linea-Scala CFX	
			Insert Type	2 gang Multi-Way Touch Slave Controller	
			Plate Finish	Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze	
			Insert Colour	Black Nickel/Black	
			EAN13 Barcode	5017504060848	
			Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
			Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
			Minimum Wall Box Depth	35mm	
			Wattage	The same as Touch Master or Ceiling Dimmer	
			Switched Poles	N/A	
			Current Rating	The same as Touch Master or Ceiling Dimmer	
			Voltage	220/250V AC	
			Maximum Load	The same as Touch Master	
			Mains Frequency	50Hz	
			IP Rating	IP2XD	
			Contact Gap Minimum	N/A	
Terminal Capacity 1	2 x 1mm ²				
Terminal Capacity 2	2 x 1.5mm ²				
Earth Terminal Capacity 1	5 x 1mm ²				
Earth Terminal Capacity 2	4 x 1.5mm ²				
Earth Terminal Capacity 3	3 x 2.5mm ²				
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand				
Earth Terminal Capacity 5	1 x 6mm ²				
Product Class 1	Face plate must be earthed				
Ambient Operating Temperature	-5° to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN 60669-2-1				
Additional Notes	<p>Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers</p>				

LSX2XTSRB-RBB

Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze Front 2 gang Multi-Way Touch Slave Controller Black Nickel/Black

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:33 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. 14012238