

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSX3XTSBC-BSW

| Linea-Scala CFX Bright Chrome Frame/Bright Steel Front 3 gang Multi-Way Touch Slave Controller Bright Chrome/White | | | | |
|--------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|--|--|
| Item Image | Wiring | Dimensions | | |
| | Multi-Way Wiring using Slave module(s) | LINEA SCALA CFX 3XTS Multi-WayTouch Slave Controller | | |
| Primary Range | Linea-Scala CFX | | | |
| Insert Type | 3 gang Multi-Way Touch Slave Controller | | | |
| Plate Finish | Linea-Scala CFX Bright Chrome Frame/Bright Steel | | | |
| Insert Colour | Bright Chrome/White | | | |
| EAN13 Barcode | 5017504700591 | | | |
| Dimensions (Nominal) | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm | | | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | | | |
| Minimum Wall Box Depth | 35mm | | | |
| Wattage | The same as Touch Master or Ceiling Dimmer | | | |
| Switched Poles | N/A | | | |
| Current Rating | The same as Touch Master or Ceiling Dimmer | | | |
| Voltage | 220/250V AC | | | |
| Maximum Load | The same as Touch Master | | | |
| Mains Frequency | 50Hz | | | |
| IP Rating | IP2XD | | | |
| Contact Gap Minimum | N/A | | | |
| Terminal Capacity 1 | 2 x 1mm2 | | | |
| Terminal Capacity 2 | 2 x 1.5mm2 | | | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | | | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | | |
| Product Class 1 | Face plate must be earthed | | | |
| Ambient Operating Temperature | -5° to +40°C | | | |
| Recommended Location | Internal Use Only | | | |
| Maximum Installation Altitude | 2000m | | | |
| Standard/Approval Additional Notes | BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers | | | |



SL

making connections beautifully

| LCV2VTCD | O DOW | |
|----------|-------|--|

LSX3X1SBC-BSW

Linea-Scala CFX Bright Chrome Frame/Bright Steel Front 3 gang Multi-Way Touch Slave Controller Bright Chrome/White

| Einea deala of A Bright Official France Bright Octobrition of garig Maila Way Fouch Clave Controller Bright Official Controller | | | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 | | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 08:34 AM E&OE | | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Wiring.









