

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSX45SS1BC-BKB

Linea-Scala CFX Bright Chrome Frame/Black Nickel Front 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Bright Chrome/Black

	Onionic/Black	
Item Image	Wiring	Dimensions
	Load NO	Hemilton LINEA SCALA CFX 45SS1 Double Pole Red Rocker & Neon & 13A Switched Socket
Primary Range	Linea-Scala CFX	
Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socket	
Plate Finish	Linea-Scala CFX Bright Chrome Frame/Black Nickel	
Insert Colour	Red+Bright Chrome/Black	
EAN13 Barcode	5017504592707	
Dimensions (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	Switch 45 Amp Socket 13 Amp	
Voltage	220/250V AC	
Maximum Load	Switch 45 Amp Socket 13	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3 x 6mm2	
Terminal Capacity 2	2 x 10mm2	
Terminal Capacity 3	1 x 16mm2	
Earth Terminal Capacity 1	3 x 6mm2	
Earth Terminal Capacity 2	2 x 10mm2 1 x 16mm2	
Earth Terminal Capacity 3 Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 4177	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:34 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84











