

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSX45SS1PB-BSW

Linea-Scala CFX Polished Brass Frame/Bright Steel Front 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Polished Brass/White

Item Image Wiring **Dimensions** Hamilton Linea-Scala CFX Primary Range Insert Type 45A Double Pole Red Rocker + Neon + 13A Switched Socket Linea-Scala CFX Polished Brass Frame/Bright Steel Plate Finish Insert Colour Red+Polished Brass/White EAN13 Barcode 5017504633707 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double **Current Rating** Switch 45 Amp Socket 13 Amp 220/250V AC Voltage Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 It is the policy of the company to improve products as part of our development programme. All products listed conform to current British or All accessories are manufactured under an accredited European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 17 October 2018 08:34 AM the limitations of reproduction and printing process and are not binding. guarantee an exact colour match and shadings of of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











