

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSX4XLEDITB100HB-HB

Linea-Scala CFX Connaught Bronze Frame/Connaught Bronze 4g 100W LED 2 Way Push On/Off Rotary Dimmer Connaught Bronze

Primary Range Linea-Scala CFX Insert Type A gang 100W LED Trailing/Leading Plate Finish Linea-Scala CFX Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode Dimensions (Nominal) Double: Height = 91.5mm Width = Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = Minimum Wall Box Depth Wattage Switched Poles Single Current Rating Voltage 230V-240V Maximum Load Mains Frequency Switz	Dimensions  Hamilton LINEA SCALA CFX 4XLEDITB LEDITB100 2 Way Dimmer	
Insert Type 4 gang 100W LED Trailing/Leading Plate Finish Linea-Scala CFX Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504085858 Dimensions (Nominal) Double: Height = 91.5mm Width = Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing: Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang	LEDITB100 2 Way Dimmer	
Insert Type 4 gang 100W LED Trailing/Leading Plate Finish Linea-Scala CFX Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504085858 Dimensions (Nominal) Double: Height = 91.5mm Width = Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing: Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang	150.5	
Insert Type 4 gang 100W LED Trailing/Leading Plate Finish Linea-Scala CFX Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504085858 Dimensions (Nominal) Double: Height = 91.5mm Width = Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing: Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang		
Plate Finish Linea-Scala CFX Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504085858 Dimensions (Nominal) Double: Height = 91.5mm Width = Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing : Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang		
Insert Colour	Edge Push On/Off Rotary 2 Way Switching Dimmer	
EAN13 Barcode         5017504085858           Dimensions (Nominal)         Double: Height = 91.5mm Width	e Frame/Connaught Bronze	
Dimensions (Nominal)  Fixing Hole Centres  Box Fixing = 120.6mm Grid Fixing :  Minimum Wall Box Depth  35mm  Wattage  5-70W Per Gang  Switched Poles  Current Rating  Voltage  230V-240V  Maximum Load  Double: Height = 91.5mm Width =  Box Fixing = 120.6mm Grid Fixing :  Single  0.3A Per Gang  230V-240V		
Fixing Hole Centres         Box Fixing = 120.6mm         Grid Fixing =           Minimum Wall Box Depth         35mm           Wattage         5-70W Per Gang           Switched Poles         Single           Current Rating         0.3A Per Gang           Voltage         230V-240V           Maximum Load         5-70W Per Gang		
Minimum Wall Box Depth         35mm           Wattage         5-70W Per Gang           Switched Poles         Single           Current Rating         0.3A Per Gang           Voltage         230V-240V           Maximum Load         5-70W Per Gang	= 150.5mm Depth = 4.0mm	
Wattage         5-70W Per Gang           Switched Poles         Single           Current Rating         0.3A Per Gang           Voltage         230V-240V           Maximum Load         5-70W Per Gang	= CFX Clips	
Switched Poles         Single           Current Rating         0.3A Per Gang           Voltage         230V-240V           Maximum Load         5-70W Per Gang		
Current Rating         0.3A Per Gang           Voltage         230V-240V           Maximum Load         5-70W Per Gang		
Voltage         230V-240V           Maximum Load         5-70W Per Gang		
Maximum Load 5-70W Per Gang		
Mains Frequency 50Hz		
IP Rating IP2XD		
Terminal Capacity 1 2X1mm <sup>2</sup>		
Terminal Capacity 2 2X1.5mm <sup>2</sup>		
Earth Terminal Capacity 1 5X1mm <sup>2</sup>		
Earth Terminal Capacity 2 4X1.5mm <sup>2</sup>		
Earth Terminal Capacity 3 3X2.5mm <sup>2</sup>		
Earth Terminal Capacity 4 1X4mm² Multi-Strand		
Earth Terminal Capacity 5 1X6mm <sup>2</sup>		
Product Class 1 Face plate muct be earthed		
Ambient Operating Temperature -5°C to +40°C		
Recommended Location Internal Use Only		
Maximum Installation Altitude 2000m		
Standard/Approval BS EN 60669-2-1		
Additional Notes Trailing Edge & Leading Edge Dimm	ner	
Patents and Trademarks CFX is a Registered Trade Mark No	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured in the BS EN ISO 9001 : 2015 Quality Manufactured in the BS EN ISO 9001 :		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  Due to manufacturing proces guarantee an exact colour mate of certain finishe	·	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio