SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSX5258SN-BSW

Linea-Scala CFX Satin Nickel Frame/Bright Steel Front 1 gang 15A 110V AC American Unswitched Socket White

the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	Linea-Scala CFX Satin Nickel Fra	me/Bright Steel Front 1 gang 15A 110V AC	American Unswitched Socket White	
Primary Range Linea-Scala CFX Insert Type 1 gang 15A 110V AC American Unswitched Socket Insert Colour White EAN13 Barcode 5017504061890 Unea-Scala CFX Satin Nicket FrameBright Steel Insert Colour White EAN13 Barcode 5017504061890 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Single: Height = 91.5mm Depth = 4.0mm Single:	Item Image	Wiring	Hamilton Linea scala cfx	
Insert Type			Unswitched American Socket	
Plate Finish Linea-Scala CFX Satin Nickel Frame/Bright Steel Insert Colour White EAN13 Barcode 5017504061890 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes All products listed conform to current British or European standard and the product information is correct at the time of going to press and disgrams are reproducted minimum on the limitations of reproduction and printing process and and onto brinding of certain fliebles. But the product of an and printing processes we cannot guarantee an exact Colour match and shadings of certain fliebles.				
Insert Colour White EAN13 Barcode 5017504061890 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Walls Frequency 60Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes All products listed conform to current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is				
EAN13 Barcode 5017504061890 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IPZXD Contact Gap Minimum None Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5" to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Be N ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of or certain fliches.		· · · · · · · · · · · · · · · · · · ·		
Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IPZXD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 1 x 6mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Frequency Frequency Frequency Frequency Freminal Capacity 3 1 x 6mm2 Multi-strand Freminal Capacity 3 1 x 6mm2 Multi-strand Frace plate must be earthed Ambient Operating Temperature Frequency Frequency Frequency Frequency Frequency Frequency Freminal Capacity 3 1 x 6mm2 Multi-strand Freduct Class 1 Face plate must be earthed Ambient Operating Temperature Frequency Freminal Capacity 3 Frequency Freminal Capacity 3 Freduct Class 1 Face plate must be earthed Frequency Frequency Frequency Frequency Frequency Frequency Freminal Capacity 3 Frequency Freminal Capacity 3 Freduct Class 1 Face plate must be earthed Frequency				
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz 1P Rating 1P2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Additional Notes All products listed conform to current British or European standard and the product information is correct at the time of gloing to press. All products listed conform to current British or European standard and the product information is correct at the time of gloing to press. All products listed conform to current British or European standard and the product information is correct at the time of gloing to press. All products listed conform to current British or European standard and the product information is correct at the time of gloing to press. All products listed conform to current British or European standard and the product information is correct at the time of gloing to press. All products listed conform to current British or European standard and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Beautiful Products at 17 October 2018 08:35. Extra Correct and Correct and Correct and East Standard and shadings of of certain finishes.	EAN13 Barcode			
Minimum Wall Box Depth 35mm Switched Poles None Current Rating 15 Amp Voltage 110 V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IP2XID Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered: Yes Additional Notes Shuttered: Yes All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BALL Cocket Scale	Dimensions (Nominal)			
Switched Poles None Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea Ferlina CFX SS2 Is a UK Registered Design Certificate No. 2066688 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But to the manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 15 Amp Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating 1P2DD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Lines is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 239	Minimum Wall Box Depth	35mm		
Voltage 110V AC Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 2 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5' to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B Linea is a Registered Trade Mark No 2398667 Patent No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:35, Est	Switched Poles	None		
Maximum Load 15 Amp Mains Frequency 60Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Patents and Trademarks Additional Notes All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But Illustrations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of Cerret as at 17 October 2018 08:35, E&t Correct as at 17 Oc	Current Rating	15 Amp		
Mains Frequency IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain flishes.	Voltage	110V AC		
IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Blustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Maximum Load	15 Amp		
Contact Gap Minimum None Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:35 of certain finishes.	Mains Frequency	60Hz		
Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea is a Registered Trade Mark No 2398667 Patent No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Correct as at 17 October 2018 08:35 guarantee an exact colour match and shadings of process and are not binding.	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 6 Terminal	Contact Gap Minimum	None		
Terminal Capacity 3 1 x 6mm2 Multi-strand Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Correct as at 17 October 2018 08:35 / Gertain finishes.	Terminal Capacity 1	3 x 2.5mm2	3 x 2.5mm2	
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All stream of the imitations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Face plate must be earthed -5° to +40°C Internal Use Only Internal Use Only ABS EN ISO 5733 IEC60884-1 Shuttered :Yes CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Terminal Capacity 2	2 x 4mm2		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes BS EN ISO 5733 IEC60884-1 Additional Notes CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea is a Registered Trade Mark No 2398667 Patent No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Correct as at 17 October 2018 08:35 of certain finishes.	Terminal Capacity 3	1 x 6mm2 Multi-strand	1 x 6mm2 Multi-strand	
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered :Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Product Class 1	Face plate must be earthed		
Maximum Installation Altitude Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered : Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval Additional Notes Shuttered :Yes Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Recommended Location	Internal Use Only		
Additional Notes Shuttered :Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:35 of certain finishes.	Maximum Installation Altitude	2000m		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 08:35 of certain finishes.	Standard/Approval	BS EN ISO 5733 IEC60884-1		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Additional Notes	Shuttered :Yes		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.		CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588		
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd. Unit 10 Carrick Business Centre. 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:35 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Reg E: info@hamilton-litestat.com www.hamilton-litestat.com Reg

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











