## Hamilton

## making connections beautifully

SL

| JL .  | Thanking coninc  | Stion is beautifully   |  |
|---|--|--|--|
|   | Wiring Accessories • Circuit Protection • Sr   | mart Lighting Control & Multi-room Audio   |  |
| LSX5320SB-SSB   |  |  |  |
|   |  |  |  |
| Linea-Scala CFX Satin Brass Frame/Satin Steel Front 2 gang 15A 110V AC American Unswitched Socket Black   |  |  |  |
| Item Image  | Wiring   | Dimensions   |  |
|   |  | Diswitched American Socket   |  |
| Primary Range   | Linea-Scala CFX  |  |  |
| Insert Type   | 2 gang 15A 110V AC American Unswitched Socket  |  |  |
| Plate Finish  | Linea-Scala CFX Satin Brass Frame/Satin Steel  |  |  |
| Insert Colour   | Black  |  |  |
| EAN13 Barcode   | 5017504062422  |  |  |
| Dimensions (Nominal)  | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  |  |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |  |  |
| Minimum Wall Box Depth  | 35mm   |  |  |
| Switched Poles  | None   |  |  |
| Current Rating  | 15 Amp   |  |  |
| Voltage   | 110V AC  |  |  |
| Maximum Load  | 15 Amp   |  |  |
| Mains Frequency   | 60Hz   |  |  |
| IP Rating   | IP2XD  |  |  |
| Contact Gap Minimum   | None   |  |  |
| Terminal Capacity 1   | 3 x 2.5mm2   |  |  |
| Terminal Capacity 2   | 2 x 4mm2   |  |  |
| Terminal Capacity 3   | 1 x 6mm2 Multi-strand  |  |  |
| Product Class 1   | Face plate must be earthed   |  |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |  |
| Recommended Location  | Internal Use Only  |  |  |
| Maximum Installation Altitude   | 2000m  |  |  |
| Standard/Approval   | BS EN ISO 5733 IEC60884-1  |  |  |
| Additional Notes  | Shuttered :Yes   |  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.   | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.  | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.  | Correct as at 17 October 2018 08:35 AM<br>E&OE   |  |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F<br>T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered<br>E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | Road, Brislington, Bristol, BS4 5NZ<br>Office 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>n London No. 941624 VAT Registration No. 222 6607 84                                       | LUCKINS In Strington Product Selector Dissipation (CR: No. Mul238  |  |