Hamilton

making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LSX6126BC-BSW Linea-Scala CFX Bright Chrome Frame/Bright Steel Front 1 gang 10/16A 220/250V AC German Unswitched Socket White					
			5		
			Item Image	Wiring	Dimensions
7					
		Unswitched German Socket			
		→ F 49			
		91.5 50.0			
	Note: This socket in Non Polarised				
Primary Range	Linea-Scala CFX				
Insert Type	1 gang 10/16A 220/250V AC German Unswitched Socket				
Plate Finish	Linea-Scala CFX Bright Chrome Frame/Bright Steel				
Insert Colour	White				
EAN13 Barcode	5017504062521				
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm				
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth	47mm				
Switched Poles	None				
Current Rating	10/16 Amp				
Voltage	220/250V AC				
Maximum Load	16 Amp				
Mains Frequency	50Hz				
IP Rating	IP2XD				
Contact Gap Minimum	None				
Terminal Capacity 1	3 x 2.5mm2				
Terminal Capacity 2	3 x4mm2				
Terminal Capacity 3	2 x 6mm2 Multi-Strand				
Terminal Capacity 4	1 x 10mm2				
Product Class 1	Face plate must be earthed				
Ambient Operating Temperature	-5° to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN ISO 5733 IEC60884-1				
Additional Notes	Shuttered:Yes				
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:35 AM E&OI			
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered C E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	Dad, Brislington, Bristol, BS4 5NZ Mice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimble product selector Display (Cart No. 1401)			