SL

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXDENTPB-ABW

Linea-Scala CFX Polished Brass Frame/Antique Brass Front Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) White

Item Image







Dimensions



| | OMAÇÎ DANEN | |
|---|--|--|
| Primary Range | Linea-Scala CFX | |
| Insert Type | Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) | |
| Plate Finish | Linea-Scala CFX Polished Brass Frame/Antique Brass | |
| Insert Colour | White | |
| EAN13 Barcode | 5017504620080 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| EuroFix Additional Notes | Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) | |
| Frequencies 1 | TV=5-68 MHz 125-860 MHz | |
| Frequencies 2 | FM=88-108 MHz | |
| Frequencies 3 | SAT DC=950-2200 MHz | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 08:36 AM E&OE |
| | | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











