SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXDSAT+SB-SSB

Linea-Scala CFX Satin Brass Frame/Satin Steel Front Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible) Black

Item Image Wiring **Dimensions** Hamilton Primary Range Linea-Scala CFX Insert Type Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible) Plate Finish Linea-Scala CFX Satin Brass Frame/Satin Steel Insert Colour Black EAN13 Barcode 5017504661090 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Box Fixing = 120.6mm Grid Fixing = CFX Clips Fixing Hole Centres Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 **Ambient Operating Temperature** -5° to +40°C Internal Use Only Recommended Location Maximum Installation Altitude 2000m Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) plus Telephone Slave and Female TV EuroFix Additional Notes Socket Frequencies 1 TV=5-68 MHz 125-860 MHz Frequencies 2 FM=88-108 MHz SAT DC=950-2200 MHz Frequencies 3 Frequencies 4 TV DC=5-2200 MHz Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products European standard and the product information is as part of our development programme. correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:37 AM E&OE process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

+44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84









