SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXDTRIDEB-EBB

Linea-Scala CFX Etrium Bronze Frame/Etrium Bronze Front Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible)

Black

Black		
Item Image	Wiring	Dimensions
	® ● ● ○ ■ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○	Hemilton LINEA SCALA CFX DTRID Non-Isolated TV/FM/Satellite1 Triplexer 1in/3out
	1. Undo the cable clamp screw. 2. Lift up the cover of the clamp, be careful not to displace the control of the cable clamp screw. 3. In early the conductor fine the terminal and which is located in the casing of the module. 4. Surfer clamp for cover check to ensure that conductor. 5. Carefully close the cover of the conductor period as a threw below. 6. Carefully close the cover of the module searing that the EMC period cover check to ensure that conductor. 6. Carefully close the cover of the module searing that the EMC period cover of the cover of the module searing that the EMC period cover of the co	91.5 91.5 90.0 ——————————————————————————————————
Primary Range	Linea-Scala CFX	
Insert Type	Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible)	
Plate Finish	Linea-Scala CFX Etrium Bronze Frame/Etrium Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504063726	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Triplexer for use with combined TV FM and Satellite Signal (DAB compatible)	
Frequencies 1	TV=5-68 MHz 125-860 MHz	
Frequencies 2	FM=88-108 MHz	
Frequencies 3	SAT DC=950-2200 MHz	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:37 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in Lon

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









