Jamilton

SL	making conne	ections beautifully
	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
	LSXDTRIDPB-SBB	The opening control at later oon Addio
Linea-Scala CFX Polished Brass Frame/Satin Brass Front Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible) Black		
Linea-Scala CFX Polished Brass Frame/	Satin Brass Front Non-Isolated TV+FM+SAT	Triplexer 1in/3out (DAB Compatible) Black
Item Image	Wiring	Dimensions
		Hemilton LINEA SCALA CFX DTRID Non-Isolated TV/FM/Satellite1 Triplexer 1in/3out
TV FM/DAB	 Under the scalar starm storm. List get has careful and to scample and to be place the EMC gasket which is bucated on the corver. Insert the conductor frint: the therminal side which is located in Bend gasket which is bucched on the corver. Bend gasket which is bucched on the corver of the module service place the store consistence of the module service place the corver of the module service place the store gasket which is bucched or damaget. Then tighten the cable careful placed or damaget. 	
Primary Range	Linea-Scala CFX	
Insert Type	Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible)	
Plate Finish	Linea-Scala CFX Polished Brass Frame/Satin Brass	
Insert Colour	Black	
EAN13 Barcode	5017504063801	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m Triplever for use with combined TV. EM and Sotellite Signal (DAB competible)	
EuroFix Additional Notes	Triplexer for use with combined TV FM and Satellite Signal (DAB compatible)	
Frequencies 1	TV=5-68 MHz 125-860 MHz FM=88-108 MHz	
Frequencies 2 Frequencies 3	SAT DC=950-2200 MHz	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:37 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com wwww.hamilton-litestat.com wwww.hamilton-litestat.com www.hamilton-li		