Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXFNHB-HBR Linea-Scala CFX Connaught Bronze Frame/Connaught Bronze Front 1 gang 13A Fuse with Neon Halo Connaught Bronze/Red Item Image Wiring Dimensions Hemilton FN Fuse with Red Neon Halo æ 4.0 -16.0 13A 250V BS5733 Linea-Scala CFX Primary Range Insert Type 1 gang 13A Fuse with Red Neon Halo Plate Finish Linea-Scala CFX Connaught Bronze Frame/Connaught Bronze Insert Colour Connaught Bronze/Red EAN13 Barcode 5017504064624 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp 220/250V AC Voltage Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 3 x 2 5mm2 **Terminal Capacity 2** 2 x 4mm2 Multi Strand **Terminal Capacity 3** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed -5° to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 17 October 2018 08:38 AM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding. of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble **SECA** T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 E: info@hamilton-litestat.com www.hamilton-litestat.com

SL