making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXFNPB-BSR

| LSXFNPB-BSR  |  |  |
|--|--|--|
| Linea-Scala CFX Polished Brass Frame/Bright Steel Front 1 gang 13A Fuse with Neon Halo Polished Brass/Red  |  |  |
| Item Image   | Wiring   | Dimensions   |
| AUSE DE LA CONTRACTION DE LA C | Live Neutral IN Neutral To Load Load   | Hemiton LINEA SCALA CFX FN Fuse with Red Neon Halo   |
| Primary Range  | Linea-Scala CFX  |  |
| Insert Type  | 1 gang 13A Fuse with Red Neon Halo   |  |
| Plate Finish   | Linea-Scala CFX Polished Brass Frame/Bright Steel  |  |
| Insert Colour  | Polished Brass/Red   |  |
| EAN13 Barcode  | 5017504632069  |  |
| Dimensions (Nominal)   | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm   |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth   | 35mm   |  |
| Switched Poles   | None   |  |
| Current Rating   | 13 Amp   |  |
| Voltage  | 220/250V AC  |  |
| Maximum Load   | 13 Amp   |  |
| Mains Frequency  | 50Hz   |  |
| IP Rating  | IP2XD  |  |
| Contact Gap Minimum  | 3mm  |  |
| Terminal Capacity 1  | 3 x 2.5mm2   |  |
| Terminal Capacity 2  | 2 x 4mm2 Multi Strand  |  |
| Terminal Capacity 3  | 1 x 6mm2   |  |
| Earth Terminal Capacity 1  | 6 x 1mm2   |  |
| Earth Terminal Capacity 2  | 5 x 1.5mm2   |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2   |  |
| Earth Terminal Capacity 4  | 2 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5  | 1 x 6mm2   |  |
| Product Class 1  | Must be earthed  |  |
| Ambient Operating Temperature  | -5° to +40°C   |  |
| Recommended Location   | Internal Use Only  |  |
| Maximum Installation Altitude  | 2000m  |  |
| Standard/Approval  | BS 5733 with Fuselink to BS1362  |  |
| Patents and Trademarks   | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.  | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 08:38 AM<br>E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1770 710414

Registered Office 1 Rushmills Berford Road, Norther

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









