Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio
LSXJ12HB-HBB		
Linea-Scala CFX Connaught Bronze Frame/Connaught Bronze Front 1 gang RJ12 Outlet - Unshielded Black		
		_
Item Image	Wiring	Dimensions
		• •»
		Hemilton Linea scala cfx
	Datacom Module Rear View View of Transparent Cover	J12 1 gang RJ12 Outlet Unshielded 6 wire
	Ustacom Module Rear View View of Transparent Cover RJ11/12 Socket Rear View 0133 4 5 6 0	
		91.5
	Cable tie	
	SNI SLIT 12 Million Calture College Not Struct With Calture College Not Struct Webs 1 College V Write 1 College V Write 1 College V Write 1 College V Write	91.5
	2 ORANGE (White Fillue 3 WHTE Fillue 4 BLUE / White RED 5 WHTE For Chamb Burker 6 WHTE For Chamb Burker	
	O INOT USED Moint UseD Main Wire Colour shown in CAPITALS	
Primary Range	Linea-Scala CFX	
Insert Type	1 gang RJ12 Outlet - Unshielded	
Plate Finish	Linea-Scala CFX Connaught Bronze Frame/Connaught Bronze Black	
Insert Colour		
EAN13 Barcode	5017504064679	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm N/A	
Switched Poles	IP2XD	
IP Rating Contact Gap Minimum	N/A	
	5 x 1mm2	
Earth Terminal Capacity 1	4 x 1.5mm2	
Earth Terminal Capacity 2 Earth Terminal Capacity 3	4 x 1.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:38 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered C E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	LISTED IN STRIMULE LUCKINS Product Selector DISSPILE (CR. No. 104128

SL