




## LSXJ12PB-SSW

### Linea-Scala CFX Polished Brass Frame/Satin Steel Front 1 gang RJ12 Outlet - Unshielded White

| Item Image  | Wiring   | Dimensions |        |        |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
|---|--|------------|--------|--------|--------|--------|-------|--------|--------|--------|--------|---|---------------|------|------|------|---|----------------|--------|-------|-------|---|--------------|-----|-----|-----|---|--------------|-------|-------|-------|---|----------------|--------|--------|--------|---|--------|--------|--------|--------|---|
|  |  <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>RIGHT</th> <th>LEFT</th> <th>Wiring</th> <th>Colour</th> <th>Socket</th> </tr> </thead> <tbody> <tr> <td>No. 0</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>1</td> <td>GREEN / White</td> <td>BLUE</td> <td>BLUE</td> <td>BLUE</td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>YELLOW</td> <td>GREEN</td> <td>GREEN</td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>RED</td> <td>RED</td> <td>RED</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>BLACK</td> <td>BLACK</td> <td>BLACK</td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>6</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> </tbody> </table> | RIGHT      | LEFT   | Wiring | Colour | Socket | No. 0 | NO USE | NO USE | NO USE | NO USE | 1 | GREEN / White | BLUE | BLUE | BLUE | 2 | ORANGE / White | YELLOW | GREEN | GREEN | 3 | WHITE / Blue | RED | RED | RED | 4 | BLUE / White | BLACK | BLACK | BLACK | 5 | WHITE / Orange | NO USE | NO USE | NO USE | 6 | NO USE | NO USE | NO USE | NO USE |  <p data-bbox="1230 457 1399 533"><b>Hamilton</b><br/>LINEA SCALA CFX<br/>J12<br/>1 gang RJ12 Outlet Unshielded 6 wire</p> |
| RIGHT   | LEFT   | Wiring     | Colour | Socket |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| No. 0   | NO USE   | NO USE     | NO USE | NO USE |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| 1   | GREEN / White  | BLUE       | BLUE   | BLUE   |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| 2   | ORANGE / White   | YELLOW     | GREEN  | GREEN  |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| 3   | WHITE / Blue   | RED        | RED    | RED    |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| 4   | BLUE / White   | BLACK      | BLACK  | BLACK  |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| 5   | WHITE / Orange   | NO USE     | NO USE | NO USE |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |
| 6   | NO USE   | NO USE     | NO USE | NO USE |        |        |       |        |        |        |        |   |               |      |      |      |   |                |        |       |       |   |              |     |     |     |   |              |       |       |       |   |                |        |        |        |   |        |        |        |        |   |

|   |  |   |
|---|--|---|
| Primary Range   | Linea-Scala CFX  |   |
| Insert Type   | 1 gang RJ12 Outlet - Unshielded  |   |
| Plate Finish  | Linea-Scala CFX Polished Brass Frame/Satin Steel   |   |
| Insert Colour   | White  |   |
| EAN13 Barcode   | 5017504640552  |   |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm   |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Switched Poles  | N/A  |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | N/A  |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| EuroFix Additional Notes  | Can be used as either RJ11 (4 wires) or RJ12 (6 wires)   |   |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 08:38 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **LUCKINS**



CERT. No. FM12138