




LSXJ45BC-SSB

Linea-Scala CFX Bright Chrome Frame/Satin Steel Front 1 gang RJ45 CAT 5E Outlet - Unshielded Black

| Item Image | Wiring | Dimensions | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|----------------|---------------------|--------------|-------------|---|---------------|----------------|--------|---|---------------|----------------|-------|---|----------------|---------------|------|---|--------------|--------------|-------|---|--------------|--------------|------|---|----------------|----------------|-------|---|---------------|---------------|-------|---|---------------|---------------|-------|---|
|  |  <p>RJ45 CAT5e and CAT6 Wiring Colour Codes</p> <table border="1" data-bbox="803 583 966 672"> <thead> <tr> <th>Pin</th> <th>EIA Wiring Schedule</th> <th>Colour Codes</th> <th>ISDN Colour</th> </tr> </thead> <tbody> <tr><td>1</td><td>WHITE / Green</td><td>WHITE / Orange</td><td>Orange</td></tr> <tr><td>2</td><td>GREEN / White</td><td>ORANGE / White</td><td>Green</td></tr> <tr><td>3</td><td>WHITE / Orange</td><td>WHITE / Green</td><td>Blue</td></tr> <tr><td>4</td><td>BLUE / White</td><td>BLUE / White</td><td>White</td></tr> <tr><td>5</td><td>WHITE / Blue</td><td>WHITE / Blue</td><td>Blue</td></tr> <tr><td>6</td><td>ORANGE / White</td><td>WHITE / Orange</td><td>White</td></tr> <tr><td>7</td><td>WHITE / Brown</td><td>WHITE / Brown</td><td>Brown</td></tr> <tr><td>8</td><td>BROWN / White</td><td>BROWN / White</td><td>Brown</td></tr> </tbody> </table> <p>Please always check with the colour coding found on the product.</p> | Pin | EIA Wiring Schedule | Colour Codes | ISDN Colour | 1 | WHITE / Green | WHITE / Orange | Orange | 2 | GREEN / White | ORANGE / White | Green | 3 | WHITE / Orange | WHITE / Green | Blue | 4 | BLUE / White | BLUE / White | White | 5 | WHITE / Blue | WHITE / Blue | Blue | 6 | ORANGE / White | WHITE / Orange | White | 7 | WHITE / Brown | WHITE / Brown | Brown | 8 | BROWN / White | BROWN / White | Brown |  |
| Pin | EIA Wiring Schedule | Colour Codes | ISDN Colour | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | WHITE / Green | WHITE / Orange | Orange | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | GREEN / White | ORANGE / White | Green | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | WHITE / Orange | WHITE / Green | Blue | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | BLUE / White | BLUE / White | White | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | WHITE / Blue | WHITE / Blue | Blue | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | ORANGE / White | WHITE / Orange | White | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | WHITE / Brown | WHITE / Brown | Brown | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | BROWN / White | BROWN / White | Brown | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|--|
| Primary Range | Linea-Scala CFX |
| Insert Type | 1 gang RJ45 CAT 5E Outlet - Unshielded |
| Plate Finish | Linea-Scala CFX Bright Chrome Frame/Satin Steel |
| Insert Colour | Black |
| EAN13 Barcode | 5017504711573 |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips |
| Minimum Wall Box Depth | 35mm |
| Switched Poles | N/A |
| IP Rating | IP2XD |
| Contact Gap Minimum | N/A |
| Earth Terminal Capacity 1 | 5 x 1mm ² |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-strand |
| Earth Terminal Capacity 5 | 1 x 6mm ² |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) |
| Ambient Operating Temperature | -5° to +40°C |
| Recommended Location | Internal Use Only |
| Maximum Installation Altitude | 2000m |
| EuroFix Additional Notes | Can be used in both EIA 568A and EIA 568B wiring schedules |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |

| | | |
|--|--|--|
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p> | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p> | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p> | <p>Correct as at 17 October 2018 08:38 AM E&OE</p> |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238