SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXJ45SB-SSW

Linea-Scala CFX Satin Brass Frame/Satin Steel Front 1 gang RJ45 CAT 5E Outlet - Unshielded White

Item Image Wiring **Dimensions** Hamilton J45 1 gang RJ45 -CAT 5E Outlet Unshielded 8 wire Linea-Scala CFX Primary Range Insert Type 1 gang RJ45 CAT 5E Outlet - Unshielded Plate Finish Linea-Scala CFX Satin Brass Frame/Satin Steel Insert Colour White EAN13 Barcode 5017504660574 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Box Fixing = 60.3mm Grid Fixing = CFX Clips Fixing Hole Centres Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) -5° to +40°C **Ambient Operating Temperature** Internal Use Only Recommended Location Maximum Installation Altitude 2000m EuroFix Additional Notes Can be used in both EIA 568A and EIA 568B wiriing schedules Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:38 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









