## Hamilton

## making connections beautifully

|   | Wiring Accessories • Circuit Protection • Sr  | mart Lighting Control & Multi-room Audio   |
|---|---|--|
|   | LSXK21PB-SSW  |  |
|   |   |  |
| Linea-Scala CFX Polishe   | ed Brass Frame/Satin Steel Front 1 gang 20A   | X 2 Way Key Switch White   |
| Item Image  | Wiring  | Dimensions   |
|   |   | Hamilton   |
|   | Antmine 2 wey setting   | LINEA SCALA CFX<br>LINEA SCALA CFX<br>K21<br>2 Way Key switch  |
|   |   | 91.5   |
| Primary Range   | Linea-Scala CFX   |  |
| Insert Type   | 1 gang 20AX 2 Way Key Switch  |  |
| Plate Finish  | Linea-Scala CFX Polished Brass Frame/Satin Steel  |  |
| nsert Colour  | White   |  |
| EAN13 Barcode   | 5017504643690   |  |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |  |
| /inimum Wall Box Depth  | 35mm  |  |
| Switched Poles  | Single  |  |
| Current Rating  | 20AX  |  |
| /oltage   | 220/250V AC   |  |
| Maximum Load  | 20 Amp inductive  |  |
| Mains Frequency   | 50Hz  |  |
| P Rating  | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 5 x 1mm2  |  |
| Ferminal Capacity 2   | 4 x 1.5mm2  |  |
| Ferminal Capacity 3   | 2 x 2.5mm2  |  |
| Ferminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Ferminal Capacity 5   | 1 x 6mm2  |  |
| Earth Terminal Capacity 1   | 6 x 1mm2  |  |
| Earth Terminal Capacity 2   | 5 x 1.5mm2  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | -5° to +40°C  |  |
| Recommended Location Maximum Installation Altitude  | 2000m   |  |
| Standard/Approval   | BS EN 60669-1   |  |
| Patents and Trademarks  | Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 206658  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.            | No. 2066588      It is the policy of the company to improve products     as part of our development programme.     Therefore, we reserve the right to alter designs     and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.                | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes. | Correct as at 17 October 2018 08:38 A<br>E&C   |

SL

LSXK21PB-SSW - Linea-Scala CFX Polished Brass Frame/Satin Steel Front 1 gang 20AX 2 Way Key Switch White

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio