

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXR212PB-ABW

| Insert Type 1 g   | Wiring  Wiring  Decea-Scala CFX  Gang 20AX 2 Way Rocker  Decea-Scala CFX Polished Brass Frame/Antique Brass  Dished Brass/White  117504623364  Ingle: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | Dimensions  Hemilton Linea Scala CFX R212 2 Way Rocker   |
|---|--|--|
| Insert Type 1 g   | gang 20AX 2 Way Rocker nea-Scala CFX Polished Brass Frame/Antique Brass plished Brass/White ph/7504623364  | R212<br>2 Way Rocker   |
| Insert Type 1 g   | gang 20AX 2 Way Rocker nea-Scala CFX Polished Brass Frame/Antique Brass plished Brass/White ph/7504623364  |  |
|   | nea-Scala CFX Polished Brass Frame/Antique Brass<br>plished Brass/White<br>pdf7504623364   |  |
| Plate Finish Lin  | olished Brass/White<br>p17504623364  |  |
|   | 17504623364  |  |
| Insert Colour Po  |  |  |
|   | ngle: Height = 91.5mm Width = 91.5mm Depth = 4.0mr   |  |
|   |  |  |
| Fixing Hole Centres Bo  | ox Fixing = 60.3mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth 35   | imm  |  |
| Switched Poles Sir  | ngle   |  |
| Current Rating 20   | AX   |  |
| Voltage 22  | 220/250V AC  |  |
| Maximum Load 20   | Amp inductive  |  |
| Mains Frequency 50  | Hz   |  |
| IP Rating IP2   | 2XD  |  |
| Contact Gap Minimum 3m  | nm   |  |
| . ,   | x 1mm2   |  |
| 1 7   | x 1.5mm2   |  |
| 1 1   | x 2.5mm2   |  |
|   | x 4mm2 Multi-strand  |  |
| 2 2 2 4 7 7 7 7   | x 6mm2   |  |
| Earth Terminal Capacity 1 6 x   | x 1mm2   |  |
| Earth Terminal Capacity 2 5 x   | x 1.5mm2   |  |
| Earth Terminal Capacity 3 3 x   | x 2.5mm2   |  |
| Earth Terminal Capacity 4 2 x   | x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5 1 x   | x 6mm2   |  |
| Product Class 1 Mu  | ust be earthed   |  |
| Ambient Operating Temperature -5°   | ° to +40°C   |  |
| Recommended Location Into   | ternal Use Only  |  |
|   | 00m  |  |
| Standard/Approval BS  | S EN 60669-1   |  |
| Patents and Trademarks CF   | nea is a Registered Trade Mark No 2398665<br>FX is a Registered Trade Mark No 2398667 Patent No. GE<br>nea-Perlina CFX SS2 is a UK Registered Design Certificato                                   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  Brislington, Bristol, BS4 5NZ   | Correct as at 17 October 2018 08:38 AM<br>E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio