

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXR21SB-SBB

Primary Range Lines-Scala CFX Insert Type 1 gam 10AX 2 Way Rocker Plate Finish Lines-Scala CFX Staffi Brass Frame/Staffi Brass	Linea-Scala CFX Satin Bra	<b>LSXR21SB-SBB</b> ass Frame/Satin Brass Front 1 gang 10AX 2 W	/ay Rocker Satin Brass/Black	
Primary Range Linea-Scala CFX Insert Type 1 gang 10AX 2 Way Rocker Plate Finish Linea-Scala CFX Satin Brass Frame/Satin	Item Image	Wiring	Dimensions	
Primary Range Insert Type 1 gang 10AX 2 Way Rocker Plate Finish Linea-Scala CFX Satin Brass Frame/Satin Brass Insert Colour Satin Brass/Black EAN13 Barcode 5017504652210 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 2200/250V AC Maximum Load 110 Amp inductive Mains Frequency IP Rating IP ZXD Contact Gap Minimum 3mm Terminal Capacity 1 1 Farminal Capacity 1 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 1 manual Capacity 1 1 x 4mm2 Multi-strand 1 sx 1 mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 4 x 1.5mm2 Earth Terminal Capacity 3 5 x 1 mm2 Earth Terminal Capacity 4 5 x 1 mm2 Earth Terminal Capacity 3 1 x 4 mm2 Earth Terminal Capacity 3 1 x 4 mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand 1 x 4 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 6 Earth Earth Capacity 6 Earth Earth Capacity 6 Earth Earth Earth Capacity 6 Earth Earth Earth Capacity 6 Earth Earth Earth Earth Earth Earth Earth Earth Ea			R21 2 Way Rocker	
Insert Type		Alternative 2 very settling Use in Long Out Intermediate settling sealer	91.5	
Plate Finish   Linea-Scala CFX Satin Brass Frame/Satin Brass				
Insert Colour		, ,		
EAN13 Barcode				
Dimensions (Nominal)         Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Maximum Erequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 6         1 x 6mm2           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 6<				
Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Forduct Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	EAN13 Barcode			
Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5" to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Dimensions (Nominal)			
Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Forduct Class 1         Must be earthed           Ambient Operating Temperature         -5" to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Minimum Wall Box Depth	25mm		
Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Switched Poles	Single		
Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Current Rating	10AX		
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Voltage	220/250V AC		
IP Rating	Maximum Load	10 Amp inductive		
Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Mains Frequency			
Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	IP Rating	IP2XD		
Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         1 x 2.5mm2           Terminal Capacity 4         1 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         5 x 1mm2           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	Contact Gap Minimum	3mm		
Terminal Capacity 3  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Forduct Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4  Terminal Capacity 5  1 x 4mm2 Multi-strand  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 4  Terminal Capacity 5  1 x 4mm2 Multi-strand  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude	Terminal Capacity 3	1 x 2.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  75° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  1 x 6mm2		1 x 4mm2 Multi-strand		
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m		1 x 6mm2		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m		5 x 1mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  3 x 2.5mm2  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  2000m	· · ·			
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m				
Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m				
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m				
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m				
Recommended Location Internal Use Only Maximum Installation Altitude 2000m				
Maximum Installation Altitude 2000m	, , ,			
Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588		Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB	3 2383375B 9 No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is	All accessories are manufactured under an accredited	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:39 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio