

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXR24SN-SSB

Primary Parage Lines-Scale CFX react Type 4 gang 10XX 2 Way Rocker Interest Color Simila Stancial Stan	Linea-Scala CFX Satin Ni	<u>LSXR24SN-SSB</u> ckel Frame/Satin Steel Front 4 gang 10AX 2 W	/ay Rocker Satin Steel/Black	
Primary Range Lineus Scala CFX Insert Type 4 Agang JANX 2 Way Rooker Patter Fishich 1. Desposable CFX Seath Inskeld Frame/Satin Steel Insert Colour Satin Steel/Black EAN1 3 Barcode 50 S17504-7202-49  Demendions (Normical) Double: Height et 91.5mm Width = 150.5mm Depth = 4.0mm  Fishing Hole Centree Box Fishing = 120.6mm, Grid Fishing = CFX Clips  Minimum Wall Box Depth 2.2mm  Switched Poles Contree Box Fishing = 120.6mm, Grid Fishing = CFX Clips  Minimum Wall Box Depth 2.2mm  Switched Poles Single  Current Rating 1.0AX  Voltage 2.20250V AC  Maximum Load 1.0AX  Voltage 1.20.25mm Single Current Rating 1.0AX  Voltage 1.20.25mm Single Current Rating 1.0AX  Terminal Capacity 2.20250V AC  Maximum Load 1.20.25mm Single Current Rating 1.0AX  Voltage 1.20.25mm Single Current R				
Insert Type  4 gang 10AX 2 Way Rocker  Linea-Scala CFX Satin Nickel Frame/Satin Steel Insert Colour  Satin Steel/Black  EAN13 Barcode  5017504726249  Dimensions (Nominal)  Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 120.6mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  25mm  Switched Poles  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating  IP PZXD  Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  1 x 6mm2  Earth Terminal Capacity 7  Earth Terminal Capacity 8  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  Earth Terminal Capacity 6  Earth Terminal Capacity 6  1 x 6mm2  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 6  Earth Terminal Capacity 9  Earth Terminal Capacity 6  Earth Ter		Afternative 2 way switching Loop in Livey Cod.	R24 2 Way Rocker	
Plate Finish Linear-Colour Satin Steel/Black EAN13 Barcode Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency FRating IP2XD Contact Gap Minimum 3mm Feminal Capacity 1 5 x tmm2 Terminal Capacity 2 5 x tmm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4.1.5mm2 Earth Terminal Capacity 1 5 x tmm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1 mm2 Earth Terminal Capacity 5 5 x 1 x 8 mm2 Froduct Class 1 Must be earthed All products listed conform to current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard a	Primary Range	Linea-Scala CFX		
Insert Colour	Insert Type	4 gang 10AX 2 Way Rocker		
EAN13 Barcode 5017504726249  Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  Fixing Hole Centres  Minimum Wall Box Depth 25mm  Switched Poles Single  Current Rating 10AX  Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating IPZXD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 3 1 x 4.5mm2  Terminal Capacity 4 1 x 4.5mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 7 1 x 6mm2  Earth Terminal Capacity 8 1 x 6mm2  Earth Terminal Capacity 9 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 7 1 x 6mm2  Earth Terminal Capacity 8 1 x 6mm2  Earth Terminal Capacity 9 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 7 1 x 6mm2  Earth Terminal Capacity 8 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 7 1 x 6mm2  Earth Terminal Capacity 7 1 x 6mm2  Earth Terminal Capacity 8 1 x 6mm2  Earth Terminal Capacity 9 1 x 6mm2  Earth Terminal Ca	Plate Finish	Linea-Scala CFX Satin Nickel Frame/Satin Steel		
Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 19 Rating PRZD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4.15mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 4.15mm2 Earth Terminal Capacity 3 1 x 4.5mm2 Earth Terminal Capacity 3 2 x 5.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Ear	Insert Colour	Satin Steel/Black		
Fixing Hole Centres   Sox Fixing = 120.6mm Grid Fixing = CFX Clips	EAN13 Barcode	5017504726249		
Minimum Wall Box Depth  Switched Poles  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  PRating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 1  1 x 4mm2 Multi-strand  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  5 x 1mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  All accessories are manufactured under an accredited BS EN 800801 : 2215 Cuallyl Menagement System.  All accessories are manufactured under an accredited BS EN 800801 : 2215 Cuallyl Menagement System.  European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN 800801 : 2215 Cuallyl Menagement System.  European standard and the product and menagement Preferoe, we reserve the right to alter designs and dimensions without prior notice.  European standard and the product and dimensions is a pair of our development programment Therefore, we reserve the right to alter designs and dimensions without prior notice.  European standard and the aceast colour mathal and shading of guarantee an eace colour mathal and shading of guarantee an eace colour mathal and shading of guarantee an eace colour mathal and shad	Dimensions (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm		
Switched Poles Current Rating 10AX Voltage 10AX Voltage 10Ammun Load 10 Amp inductive Mains Frequency 50Hz IP Rating	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Ferminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 3  1 x 4 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6 mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  1 x 2.5mm2  Earth Terminal Capacity 3  1 x 4 mm.2 Multi-strand  Earth Terminal Capacity 5  1 x 6 mm2  For University 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6 mm2  Froduct Class 1  Must be earthed  Ambient Operating Temperature  5° to 440°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  B S EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SSZ is a Ut Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  B Illustrations and diagrams are reproducted within the limitations of reproduction and printing  Pub to manufacturing processes we cannot guarantee an exact colour match and shadings of EXE	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  P Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 1 3x 2.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 1x 6mm2  Froduct Class 1 1x 6mm2  Froduct Class 1 Must be earthed  Ambient Operating Temperature 5* to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registere	Switched Poles	Single		
Maximum Load  Mains Frequency  50Hz  IP Rating  IP Rati	Current Rating	10AX		
Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1 mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  Elinea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  Elinea is a Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is a part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice.  BEEN ISO 9001: 2015 Courrent and shadings of Correct as at 17 October 2018 8840.	Voltage	220/250V AC		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Ferminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 6mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 5 1 x 6mm2 Patents and Trademarks  Patents and Trademarks  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude  Earth Terminal Capacity 6 Internal Use Only  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is so and diagrams are reproduced within the limitations of reproduction and printing		10 Amp inductive		
IP Rating	Mains Frequency			
Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  A x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  I x 4mm2 Multi-strand  Earth Terminal Capacity 4  I x 4mm2 Multi-strand  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 5  I x 6mm2  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  B S EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  B All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System and dimension without prior notice.  B Use to manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimension without prior notice.  Extending the initiations of proproduction and printing Due to manufacturing processes we cannot Correct as at 17 October 2018 08-80.				
Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 4mm2 Multi-strand  Earth Terminal Capacity 3 1 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Froduct Class 1 Must be earthed  Ambient Operating Temperature 5 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is cornect at the time of going to press.  All products listed conform to current British or European standard and the product information is cornect at the time of going to press.  All products listed conform to current British or European standard and the product information is cornect at the time of going to press.  Due to manufacturing processes we cannot Therefore, we reserve the right to alter designs and dingrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Exercises of the company to improve products and dingrams are reproduced within the limitations of reproduction and printing		3mm		
Terminal Capacity 2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 9  1 x 4mm2 Multi-strand  Earth Terminal Capacity 9  1 x 6mm2  Earth Terminal Capacity 9  Earth Terminal Capac	· · · · · · · · · · · · · · · · · · ·	5 x 1mm2		
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  In x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufacted under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Exercise Correct as at 17 October 2018 08-80.		4 x 1.5mm2		
Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  7-5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  But it is the policy of the company to improve products as pan of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  But it is the policy of the company to improve products as pan of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of		1 x 2.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 5  In x 6mm2  Product Class 1  Ambient Operating Temperature  Product Class 1  Exercise All Interval Use Only  Exercise All products Interval Use Only  Exercise All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Exercise All Products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Exercise All Products as 17 October 2018 08-40 (purantee an exact colour match and shadings of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Exercise All Products as 17 October 2018 08-40 (purantee an exact colour match and shadings of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		1 x 4mm2 Multi-strand		
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Execution and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:40 of Correct as at 17 Octobe				
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Estendard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BY SEN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 (BE)				
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  Fecommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 (B&4)				
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 (BEX)				
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  But to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.				
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 of E&A				
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BUILUSTRATIONS and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 of E&C.				
Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 registered Design Certificate No. 2066588  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Design Certificate No. 2066588  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:40 registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:40 registered Trade Mark No 2398667  Patent No. 2398667  Patent No. 298665  CFX is a Registered Trade Mark No 2398665  Linea-Perlina CFX is a Registered Trade Mark No 2398667  Patent No. 298665  CFX is a Registered Trade Mark				
Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 of E&C.				
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  BS EN ISO 9001 : 2015 Quality Management System.  Correct as at 17 October 2018 08:40 of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:40 of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.		·		
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:40 of E&I				
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of		Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:40 AM E&OE	

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio