## Hamilton

## making connections beautifully

SL

|   | ~  | out of the bound indiry  |
|---|--|--|
| 에게 다 아파 같은 것은 것을 다 않는 것이 없는 것이 없는 것이 없다.  | Wiring Accessories • Circuit Protection • Sr   | mart Lighting Control & Multi-room Audio   |
| LSXR312PB-BSW   |  |  |
| Linea-Scala CFX Polished Brass Frame/Bright Steel Front 1 gang 20AX Intermediate Rocker Polished Brass/White                                    |  |  |
|   |  |  |
| Item Image  | Wiring   | Dimensions   |
|   | 2 Way Switch<br>Switch<br>2 Way Switch<br>2 Way Switch<br>2 Way Switch<br>2 Way Switch<br>1 0 2<br>1 | HEMILTON<br>LINEA SCALA CFX<br>R312<br>Intermediate Rocker   |
| Primary Range   | Linea-Scala CFX  | <u>, p. ,</u>  |
| Insert Type   | 1 gang 20AX Intermediate Rocker  |  |
| Plate Finish  | Linea-Scala CFX Polished Brass Frame/Bright Steel  |  |
| Insert Colour   | Polished Brass/White   |  |
| EAN13 Barcode   | 5017504633349  |  |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | Single   |  |
| Current Rating  | 20AX   |  |
| Voltage   | 220/250V AC  |  |
| Maximum Load  | 20 Amp inductive   |  |
| Mains Frequency   | 50Hz   |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | 3mm  |  |
| Terminal Capacity 1   | 5 x 1mm2   |  |
| Terminal Capacity 2   | 4 x 1.5mm2   |  |
| Terminal Capacity 3   | 2 x 2.5mm2   |  |
| Terminal Capacity 4   | 2 x 4mm2 Multi-strand  |  |
| Terminal Capacity 5   | 1 x 6mm2   |  |
| Earth Terminal Capacity 1   | 6 x 1mm2   |  |
| Earth Terminal Capacity 2   | 5 x 1.5mm2   |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2   |  |
| Earth Terminal Capacity 4   | 2 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5   | 1 x 6mm2   |  |
| Product Class 1   | Must be earthed  |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS EN 60669-1  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.                | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.  | Correct as at 17 October 2018 08:40 Al<br>E&O  |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F<br>T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered                  |  | Listed in Trimble, product product Selector Carlos Indexession (Selector Carlos Indexession)   |

LSXR312PB-BSW - Linea-Scala CFX Polished Brass Frame/Bright Steel Front 1 gang 20AX Intermediate Rocker Polished Brass/White

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio