

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXR322AB-ABB

| Linea-Scala CFX Antique Brass Frame/Antique Brass Front 2 gang 20AX Intermediate Rocker Antique Brass/Black  |   |  |
|--|---|--|
| Item Image   | Wiring  | Dimensions   |
|  | 2 Way Switch Switch 2 Way Switch L1 0 12 L1 0 | Hemilton<br>LINEA SCALA CFX<br>R322<br>Intermediate Rocker   |
|  |   | 91.5   |
| Primary Range  | Linea-Scala CFX   |  |
| Insert Type  | 2 gang 20AX Intermediate Rocker   |  |
| Plate Finish   | Linea-Scala CFX Antique Brass Frame/Antique Brass   |  |
| Insert Colour  | Antique Brass/Black   |  |
| EAN13 Barcode  | 5017504682354   |  |
| Dimensions (Nominal)   | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth   | 35mm  |  |
| Switched Poles   | Single  |  |
| Current Rating   | 20AX  |  |
| Voltage  | 220/250V AC   |  |
| Maximum Load   | 20 Amp inductive  |  |
| Mains Frequency  | 50Hz  |  |
| IP Rating  | IP2XD   |  |
| Contact Gap Minimum  | 3mm   |  |
| Terminal Capacity 1  | 5 x 1mm2  |  |
| Terminal Capacity 2  | 4 x 1.5mm2  |  |
| Terminal Capacity 3  | 2 x 2.5mm2  |  |
| Terminal Capacity 4  | 2 x 4mm2 Multi-strand   |  |
| Terminal Capacity 5  | 1 x 6mm2  |  |
| Earth Terminal Capacity 1  | 6 x 1mm2  |  |
| Earth Terminal Capacity 2  | 5 x 1.5mm2  |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4  | 2 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5  | 1 x 6mm2  |  |
| Product Class 1  | Must be earthed   |  |
| Ambient Operating Temperature  | -5° to +40°C  |  |
| Recommended Location   | Internal Use Only   |  |
| Maximum Installation Altitude  | 2000m   |  |
| Standard/Approval  | BS EN 60669-1   |  |
| Patents and Trademarks   | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.  | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  P. Hamilton & Co. Ltd. Unit 10 Carriek Business Control 4.5 Republic Re- | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.   | Correct as at 17 October 2018 08:40 AM E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio