

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

	LSXR322SN-SSB			
Item Image	Linea-Scala CFX Satin Nickel Frame/Satin Steel Front 2 gang 20AX Intermediate Rocker Satin Steel/Black			
Primary Range Lines-Scalas CFX Insert Type 2, gang 20X Intermediate Rocker Primary Barcel Insert Type 2, gang 20X Intermediate Rocker Insert Colour Sain Steelellator Sain Ste				
Insert Type		2 Way Switch Switch 2 Way Switch L10 L2	LINEA SCÁLA CFX R322 R122 Intermediate Rocker	
Pate Finish				
Insert Colour Satin Steel/Black EAN13 Barcode S017504728355 Single Sort Insing + Gol Satting +				
EAN13 Barcode Sol7504728355 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 2207250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum Terminal Capacity 3 5 x 1mm2 Terminal Capacity 4 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1 x 6mm2 Earth Terminal Capacity 1 5 x 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5	Plate Finish	Linea-Scala CFX Satin Nickel Frame/Satin Steel		
Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Potes Single Current Rating 20AX Voltage 202050V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz PRating Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 9 Ear	Insert Colour	Satin Steel/Black		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips	EAN13 Barcode			
Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz 1P Rating 1P2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Sarth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1 x 5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 2 x 4mm2	Dimensions (Nominal)			
Switched Poles Current Rating 20AX 200/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 4 7 Exh 1 Sem 2 Terminal Capacity 5 1x 6mm2 Terminal Capacity 1 5x 1 fmm2 Terminal Capacity 4 2x 4 mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Terminal Capacity 6 Terminal Capacity 1 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 9 Terminal Capacit	Fixing Hole Centres			
Current Rating	Minimum Wall Box Depth			
Voltage 220/250V AC Maximur Load 20 Amp inductive Maxims Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 1 6x 1.5mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5° 10 + 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60689-1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CPX SSS 2s a UK Registered Design Certificate No. 2066588 Illustrations and diagrams are reproduction and printing corrects at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. B All products listed conform to current British or European standard and the product information is correct at the time of going to press. B All products listed conform to current British or European standard and the product information is correct at the time of going to press. B All products listed conform to current British or European standard and the product information is correct at the time of going to press. B All products listed conform to current British or European standard and the product information is correct at the time of going to press. B All products listed conform to	Switched Poles			
Maximum Load 20 Amp inductive 50Hz PRating Somma	Current Rating			
Mains Frequency 50Hz IP Rating 1P 2XD Contact Gap Minimum 5 x 1 mm2 Terminal Capacity 1 5 x 1 mm2 Terminal Capacity 2 4 x 1.5 mm2 Terminal Capacity 3 2 x 2.5 mm2 Terminal Capacity 4 2 x 4 mm2 Multi-strand Terminal Capacity 4 1 x 6 mm2 Earth Terminal Capacity 5 5 x 1.5 mm2 Earth Terminal Capacity 2 5 x 1.5 mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5 mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 9 E	Voltage			
P Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5° to 4-40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 239867 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 266588 All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press.	Mains Frequency			
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 55 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Preference and are not binding.	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 The firm and Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 The firm and Capacity 6 The fi	Contact Gap Minimum			
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Interminal Capacity 5 Earth Terminal Capacity 5 Interminal Capacity 5 Interminal Capacity 5 Interminal Capacity 5 Earth Terminal Capacity 5 Interminal Capacity 6 Earth Terminal Capacity 6 Interminal Capacity 7 Interminal Capacity 7 Interminal Capacity 7 Interminal Capacity 8 Interminal Capacity 8 Interminal Capacity 8 Interminal Capacity 9 Interminal		5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 To discontinuous 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal C	Terminal Capacity 2			
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 It x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 5 It x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 It x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 It x 6mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 It x 6mm2 Earth Terminal Capacity 9 It is the policy of the company to improve products as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ellustrations and diagrams are reproducted within the limitations of reproduction and printing processes we cannot of certain finishes.	Terminal Capacity 3			
Earth Terminal Capacity 1	Terminal Capacity 4			
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 7-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of orerain finishes. Correct as at 17 October 2018 08:40 AM E&OE or erain inishes.				
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 2			
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. Correct as at 17 October 2018 08:40 AM E&OE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:40 AM E&OE	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:40 AM E&OE	Earth Terminal Capacity 5			
Recommended Location	Product Class 1			
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature			
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:40 AM E&OE		·		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 08:40 AM E&OE of certain finishes.				
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:40 AM E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:40 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio