




## LSXSATNSB-SSW

### Linea-Scala CFX Satin Brass Frame/Satin Steel Front 1 gang Non-Isolated Satellite White

| Item Image  | Wiring   | Dimensions   |
|---|--|--|
|    |   |  <p style="text-align: center;"><b>Hamilton®</b><br/>LINEA SCALA CFX<br/>SATIN<br/>Isolated Satellite</p> |
| Primary Range   | Linea-Scala CFX  |  |
| Insert Type   | 1 gang Non-Isolated Satellite  |  |
| Plate Finish  | Linea-Scala CFX Satin Brass Frame/Satin Steel  |  |
| Insert Colour   | White  |  |
| EAN13 Barcode   | 5017504660666  |  |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | N/A  |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | N/A  |  |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |  |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |  |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |  |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.              |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 08:41 AM E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238