




## LSXSHSBC-PBW

### Linea-Scala CFX Bright Chrome Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Item Image	Wiring	Dimensions
		
Primary Range	Linea-Scala CFX	
Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)	
Plate Finish	Linea-Scala CFX Vertical Bright Chrome Frame/Polished Brass	
Insert Colour	White	
EAN13 Barcode	5017504690038	
Dimensions (Nominal)	Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	47mm	
Switched Poles	None	
Current Rating	20VA	
Voltage	220/250V AC	
Maximum Load	200/250V input; 115/230V 20VA output	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	5 x 1mm <sup>2</sup>	
Terminal Capacity 2	4 x 1.5mm <sup>2</sup>	
Terminal Capacity 3	3 x 2.5mm <sup>2</sup>	
Terminal Capacity 4	2 x 4mm <sup>2</sup> Multi-strand	
Terminal Capacity 5	1 x 6mm <sup>2</sup>	
Earth Terminal Capacity 1	9 x 1mm <sup>2</sup>	
Earth Terminal Capacity 2	6 x 1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	4 x 2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	2 x 4mm <sup>2</sup> Multi-strand	
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 61558-2-5 - BS 4573	
Additional Notes	Must be mounted vertically. Shuttered :Yes. Box Depth 47mm	

## LSXSHSBC-PBW

### Linea-Scala CFX Bright Chrome Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 17 October 2018 08:41 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FA11138