

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXSHSPB-BSB

| Linea-Scala CFX Polished Brass Frame/ | Bright Steel Front Shaver Dual Voltage Unsw                | itched Socket (Vertically Mounted) Black   |  |  |
|---------------------------------------|--|--|--|--|
| Item Image                            | Wiring   | Dimensions   |  |  |
| 2300                                  | Nontral Earth  | Hamilton LINEA SCALA CFX SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted)  159.5  159.5  159.5 |  |  |
| Primary Range                         | Linea-Scala CFX  |  |  |  |
| Insert Type                           | Shaver Dual Voltage Unswitched Socket (Vertically Mounted) |  |  |  |
| Plate Finish                          | Linea-Scala CFX Vertical Polished Brass Frame/Bright Steel |  |  |  |
| Insert Colour                         | Black  |  |  |  |
| EAN13 Barcode                         | 5017504631031  |  |  |  |
| Dimensions (Nominal)                  | Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm      |  |  |  |
| Fixing Hole Centres                   | Box Fixing = 120.6mm Grid Fixing = CFX Clips               |  |  |  |
| Minimum Wall Box Depth                | 47mm   |  |  |  |
| Switched Poles                        | None   |  |  |  |
| Current Rating                        | 20VA   |  |  |  |
| Voltage                               | 220/250V AC  |  |  |  |
| Maximum Load                          | 200/250V input; 115/230V 20VA output                       |  |  |  |
| Mains Frequency                       | 50Hz   |  |  |  |
| IP Rating                             | IP2XD  |  |  |  |
| Contact Gap Minimum                   | None   |  |  |  |
| Terminal Capacity 1                   | 5 x 1mm2   |  |  |  |
| Terminal Capacity 2                   | 4 x 1.5mm2   |  |  |  |
| Terminal Capacity 3                   | 3 x 2.5mm2   |  |  |  |
| Terminal Capacity 4                   | 2 x 4mm2 Multi-strand                                      |  |  |  |
| Terminal Capacity 5                   | 1 x 6mm2   |  |  |  |
| Earth Terminal Capacity 1             | 9 x 1mm2   |  |  |  |
| Earth Terminal Capacity 2             | 6 x 1.5mm2   |  |  |  |
| Earth Terminal Capacity 3             | 4 x 2.5mm2   |  |  |  |
| Earth Terminal Capacity 4             | 2 x 4mm2 Multi-strand                                      |  |  |  |
| Earth Terminal Capacity 5             | 1 x 6mm2   |  |  |  |
| Product Class 1                       | Must be earthed  |  |  |  |
| Ambient Operating Temperature         | -5° to +40°C   |  |  |  |
| Recommended Location                  | Internal Use Only  |  |  |  |
| Maximum Installation Altitude         | 2000m  |  |  |  |
| Standard/Approval                     | BS EN 61558-2-5 - BS 4573                                  |  |  |  |
| Additional Notes                      | Must be mounted vertically. Shuttered :Yes. Box Depth 47mm |  |  |  |
|                                       |  |  |  |  |



SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXSHSPB-BSB

Linea-Scala CFX Polished Brass Frame/Bright Steel Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

| Linea-Scala CFX Folished Blass Flame/Bright Steel Flort Shaver Dual Voltage Onswitched Socket (Vertically Mounted) Black                        |  |  |  |
|---|--|--|--|
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of   | Correct as at 17 October 2018 08:41 AM<br>E&OE   |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











