




LSXSHSPB-PBB

Linea-Scala CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |  |  |
| Primary Range | Linea-Scala CFX | |
| Insert Type | Shaver Dual Voltage Unswitched Socket (Vertically Mounted) | |
| Plate Finish | Linea-Scala CFX Vertical Polished Brass Frame/Polished Brass | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504601034 | |
| Dimensions (Nominal) | Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 47mm | |
| Switched Poles | None | |
| Current Rating | 20VA | |
| Voltage | 220/250V AC | |
| Maximum Load | 200/250V input; 115/230V 20VA output | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 5 x 1mm ² | |
| Terminal Capacity 2 | 4 x 1.5mm ² | |
| Terminal Capacity 3 | 3 x 2.5mm ² | |
| Terminal Capacity 4 | 2 x 4mm ² Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm ² | |
| Earth Terminal Capacity 1 | 9 x 1mm ² | |
| Earth Terminal Capacity 2 | 6 x 1.5mm ² | |
| Earth Terminal Capacity 3 | 4 x 2.5mm ² | |
| Earth Terminal Capacity 4 | 2 x 4mm ² Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm ² | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 61558-2-5 - BS 4573 | |
| Additional Notes | Must be mounted vertically. Shuttered :Yes. Box Depth 47mm | |

LSXSHSPB-PBB

Linea-Scala CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

| | | |
|--|---|--|
| <p>Patents and Trademarks</p> | <p>Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588</p> | |
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p> | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p> | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.</p> | <p>Correct as at 17 October 2018 08:41 AM E&OE</p> |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FA11138