

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXSHSPB-PBW

Linea-Scala CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Primary Range Lines-Scala CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Lines-Scala CFX Vertical Polished Brass Frame/Polished Brass Insert Colour White EAN13 Barcode State CFX Vertical Polished Brass Frame/Polished Brass Insert Colour White EAN13 Barcode State CFX Vertical Polished Brass Frame/Polished Brass Insert Colour White EAN13 Barcode State CFX Vertical Polished Brass Frame/Polished Brass Insert Colour White EAN13 Barcode State CFX Vertical Polished Brass Frame/Polished Brass Insert Colour Polished Brass Insert Colour State Colour Polished Brass Insert Colour State Colour State Colour Polished Brass Insert Colour State Colo	Item Image	Wiring	Dimensions	
Insert Type			Shaver Dual Voltage Unswitched Socket (Vertical Mounted) 91.5 4.0 4.0 4.0 4.0 4.0	
Plate Finish	Primary Range	Linea-Scala CFX		
Insert Colour	Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)		
EAN13 Barcode 5017504600037 Dimensions (Nominal) Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Cap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Termin	Plate Finish	Linea-Scala CFX Vertical Polished Brass Frame/Polished Brass		
Dimensions (Nominal) Double: Height = 150.5mm Width = 91.5mm Depth = 4.0mm	Insert Colour	White		
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5	EAN13 Barcode	5017504600037		
Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Dimensions (Nominal)			
Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Fixing Hole Centres			
Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Minimum Wall Box Depth	47mm		
Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-25 - BS 4573	Switched Poles	None		
Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Current Rating			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Voltage	220/250V AC		
IP Rating	Maximum Load	200/250V input; 115/230V 20VA output		
Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 7 1 x 2 x 4mm2 Multi-strand Earth Terminal Capacity 8 1 x 6mm2 Foduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Mains Frequency	50Hz		
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	IP Rating	IP2XD		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Contact Gap Minimum	None		
Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 61558-2-5 - BS 4573	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5	Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval A x 2.5mm2 2 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C Recommended Location Internal Use Only BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 1	9 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval 2 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C Recommended Location Internal Use Only BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 2	6 x 1.5mm2		
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 3	4 x 2.5mm2		
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573		Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 61558-2-5 - BS 4573	Recommended Location	Internal Use Only		
	Maximum Installation Altitude	2000m		
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm	Standard/Approval	BS EN 61558-2-5 - BS 4573		



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXSHSPB-PBW

Linea-Scala CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:41 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









