Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
	LSXSS1SB-SBW	
Linea-Scala CEX Satin Brass Fram	e/Satin Brass Front 1 gang 13A Double Pole	Switched Socket Satin Brass/White
	Broath Brass Front T gang 15A Double Fole	Switched Socket Satin Drass/White
Item Image	Wiring	Dimensions
		I I
	Neutral Earth N N N N N N N N N N N N N N N N N N N	P1.5 P1.5 P1.5 P1.5 P1.5 P1.5 P1.5 P1.5
Primary Range	Linea-Scala CFX	
Insert Type	1 gang 13A Double Pole Switched Socket	
Plate Finish	Linea-Scala CFX Satin Brass Frame/Satin Brass	
Insert Colour	Satin Brass/White	
EAN13 Barcode	5017504653019	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	13 Amp	
Voltage	220/250V AC	
Maximum Load	13 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	4 x 2.5mm2	
Terminal Capacity 2	3 x 4mm2	
Terminal Capacity 3	2 x 6mm2 Multi-Strand	
Terminal Capacity 4	1 x 10mm2	
Earth Terminal Capacity 1	4 x 2.5mm2	
Earth Terminal Capacity 2	3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 10mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2	
Additional Notes	Dual Earth: Yes	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:41 Al E&O
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered (E: info@hamilton-litestat.com www.hamilton-litestat.com	bad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Frimile LUCKINS relector

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio